

FERRIS STATE UNIVERSITY

COLLEGE OF PHARMACY

SAFETY GUIDE FOR COP LAB AND CHEMICAL SAFETY

EMERGENCY INFORMATION

EMERGENCIES

Medical Emergency - Call 911

Urgent Care Centers*

FSU Birkam Health (M-F 8AM-5PM)	1019 Campus Dr, Big Rapids	231-591-2614
Big Rapids Hospital – Spectrum Health - ER (Open 24 hours)	605 Oak St, Big Rapids	231-796-8691

*FSU Employees must visit either Birkam Health or Spectrum partners for on-the-job injuries.

Fire - Call 911 & Pull Fire Alarm:

Fire Alarm is located: Next to each building exit

Fire Extinguisher is located: In each Lab

Chemical Spill

For small spills that do not pose a threat to health or safety:

Contact Instructor, Lab Supervisor or Safety Specialists.

For large spills that may pose a threat to health or safety:

Contact Public Safety or 911

Severe Weather

Tornado Watch: Monitor weather radio

Tornado Warning: Take Shelter in lowest levels of building

CONTACTS

DIAL 911 FOR ALL EMERGENCIES

Non-Emergency:

Big Rapids Public Safety: 231-591-5000

FSU Campus Security: 231-591-5000

FSU Facilities/Physical Plant: 231-591-2920

Department Contacts

FSU Switchboard: 231-591-2000

FSU Safety Contacts

FSU Human Resources	231-591-2150
FSU Safety, Health, Environment and Risk Management (Mike McKay)	231-591-2147
Radiation Safety (Brad McCormick)	231-591-2278

Other Numbers

DTE Energy: Gas Leak: 1-800-947-5000

Consumers Power: Down Power Lines: 1-800-477-5050

Poison Control Center: 1-800-222-1222

Contents

FSU STATEMENT OF COMMITMENT	5
1.0 SCOPE	6
1.1 STATEMENT OF RESPONSIBILITY	6
1.2 CHEMICAL HYGEINE PLAN SCOPE AND APPLICATION	6
1.3 ROLES AND RESPONSIBILITIES	6
1.4 EMPLOYEE RIGHTS	7
1.5 PLAN AVAILABILITY	8
1.6 ANNUAL REVIEW	8
2.0 TRAINING	8
2.1 GENERAL AWARENESS TRAINING	8
2.2 LABORATORY-SPECIFIC TRAINING	8
2.3 METHOD OF TRAINING	9
2.4 RECORD KEEPING	9
3.0 STANDARD OPERATING PROCEDURES	10
3.1 LAB SPECIFIC STANDARD OPERATING PROCEDURES REQUIRED	10
3.2 GENERAL SAFETY PRINCIPLES	10
3.3 HEALTH AND HYGIENE	10
3.4 FOOD AND DRINK IN THE LABORATORY	11
3.5 HOUSEKEEPING	11
3.6 HAZARDOUS MATERIALS HANDLING AND STORAGE	12
3.7 TRANSFERRING OF HAZARDOUS MATERIALS	12
3.8 COMPRESSED GASSES	13
3.9 UNATTENDED OPERATIONS	13
3.10 WORKING ALONE	14
3.11 VOLUNTEERS AND GUEST SCHOLARS IN LABS	14
3.12 LABORATORY SECURITY	15
4.0 CHEMICAL HANDLING & STORAGE REQUIREMENTS	16
4.1 HAZARD IDENTIFICATION	16
4.2 LABELING	16
4.3 CHEMICALS DEVELOPED IN THE LABORATORY	17
4.4 HAZARDS SUBJECT TO REVIEW OR PRIOR APPROVAL	17
4.5 PROVISIONS FOR PARTICULARLY HAZARDOUS SUBSTANCES	18
4.6 PROVISIONS FOR PHYSICAL HAZARDS OF CHEMICALS	19
4.6.1 Flammable/Combustible Material	19
4.6.2 Corrosives	20
4.6.3 Oxidizers	20
4.6.4 Water Reactive Materials	21
4.6.5 Pyrophoric Materials	21
4.6.6 Peroxidizable Chemicals	21
4.6.7 Light Sensitive Materials	21
4.6.8 Unstable Materials	21
4.6.9 Cryogens	21
4.7 IONIZING AND NON IONIZING RADIATION AND RADIOACTIVE MATERIAL	22
4.8 BIOLOGICAL MATERIAL HAZARDS	22
5.0 LABORATORY FACILITY REQUIREMENTS	23
5.1 IDENTIFICATION OF HAZARDS	23
5.1.1 Safety Data Sheets (SDSs)	23
5.1.2 Generic Signs	23

5.1.3 Restricted Access and Designated Areas.....	23
5.1.4 Storage Areas.....	23
5.2 CONTROL MEASURES	24
5.2.1 Administrative Controls.....	24
5.2.2 Engineering Controls	24
5.3 PERSONAL PROTECTIVE EQUIPMENT	24
5.3.1 Eye and Face Protection	25
5.3.2 Protection of Skin and Body	26
5.3.3 Hearing Protection	26
5.3.4 Respiratory Protection	26
5.4 SAFETY EQUIPMENT	26
5.4.1 Safety Showers	26
5.4.2 Eyewash Facilities	26
5.4.3 First Aid Kits	27
5.4.4 Spill Kits	27
5.4.5 Fire Extinguisher	27
5.4.6 Telephone and Emergency Contact List.....	27
5.5 LABORATORY VENTILATION	27
5.5.1 Fume Hood Safe Work Practices.....	28
5.5.2 Biological Safety Cabinet Safe Work Practices	28
5.6 STANDARD REPAIR / CLOSE-OUT / DECOMMISSIONING PROCEDURES	29
6.0 HAZARDOUS WASTE MANAGEMENT PLAN	30
6.1 Waste Characterization.....	30
6.2 Container Management.....	30
6.3 Waste Disposal	30
7.0 EMERGENCY RESPONSE AND MEDICAL PROCEDURES	32
7.1 BASIC STEPS FOR EMERGENCIES AND SPILL RESPONSE.....	32
7.2 FIRE.....	32
7.3 SPILL RESPONSE.....	32
7.3.1 Minor Spills	32
7.3.2 Potentially Hazardous Spills.....	33
7.3.3 Mercury Spills	33
7.4 POWER OUTAGES.....	34
7.5 INJURY AND ILLNESS	34
7.6 MEDICAL CONSULTATIONS AND EXAMINATIONS.....	35
8.0 APPENDICES.....	36
APPENDIX A: FSU INCIDENT AND INJURY REPORT FORM.....	37
APPENDIX B: INCOMPATIBILITY OF COMMON LABORATORY CHEMICALS	38
APPENDIX C: FLAMMABLE AND COMBUSTIBLE STORAGE AND CONTAINMENT	40
APPENDIX D: COMMON LABORATORY CORROSIVES.....	42
APPENDIX E: COMMON LABORATORY OXIDIZERS	43
APPENDIX F: PEROXIDIZABLE CHEMICALS	44
APPENDIX G: SHOCK SENSITIVE AND EXPLOSIVE CHEMICALS	47
APPENDIX H: FSU CHEMICAL SAFETY LABORATORY CHECKLIST.....	48
APPENDIX I: TERMINATION OF LABORATORY USE OF HAZARDOUS MATERIALS.....	50
APPENDIX J: INDUSTRIAL TOXICOLOGY – OVERVIEW	53
APPENDIX K: FSU RESPIRATORY PROTECTION PROGRAM	56
APPENDIX L: VOLUNTEERS IN LABS TEMPLATE	62
APPENDIX M: LIST OF DEFINITIONS	65

FSU STATEMENT OF COMMITMENT

Ferris State University (FSU) is committed to providing a safe work environment for the health and well-being of its employees and students. The following Lab and Chemical Safety Guide (Plan) supports that commitment. Contained herein are the policies and procedures, prepared in accordance with State of Michigan Occupational Safety and Health Administration (MIOSHA) requirements, for the safety and health of faculty and staff while working in laboratories owned or operated by FSU.

Field work that is performed for FSU Laboratory courses or research efforts must comply with these rules; field appropriate safety plans and standard operating procedures must be developed for identified hazardous operations that occur in the field. FSU requires Units to evaluate fieldwork hazards as a part of their specific lab plans.

The Plan contains general guidelines and information about FSU's policies, safe practices, emergency response actions, and reporting forms for general use in any FSU owned/operated building where there are FSU employees. They do not, however, contain a copy of the procedures and response actions that apply to specific laboratories within a particular building. Laboratory Specific Plans and corresponding procedures are found in the relevant laboratories or by contacting a Chemical Hygiene Officer. The Laboratory Specific Plans need to be consistent with the FSU Lab Safety and Chemical Hygiene Plan.

Faculty and staff, including student employees, working in laboratory areas should become familiar with the information covered in this document. In the event of a lab related emergency, response actions and reporting procedures are documented to assure compliance with regulatory requirements and FSU policies and procedures. Emergency contact numbers are included on page two.

Although students are not included in the regulatory requirements of the MIOSHA Lab Safety Standard, FSU expects students who carry out experimental research to become familiar with the basic information contained in this Plan. FSU has delegated the responsibility for providing students with a safe learning environment to the appropriate academic administrator and faculty and staff who work with or instruct the students in the laboratories. Students are responsible for complying with the rules and regulations established by FSU for them and their colleagues' safety.

1.0 SCOPE

1.1 STATEMENT OF RESPONSIBILITY

Ferris State University (FSU), as a responsible employer, is committed to taking reasonable precautions to provide a work environment that is free from recognizable hazards for its employees and students. Because FSU academic programs include working in laboratories, the *Lab and Chemical Safety Guide* has been prepared in compliance with the Michigan Occupational Safety and Health Administration (MIOSHA) Hazardous Work in Laboratories regulation (the Laboratory Standard – Part 431). It was written to ensure that the necessary work practices, procedures, and policies are implemented to protect all employees, students, and guests working in FSU owned and operated laboratories from hazards typical of a laboratory environment.

In turn, FSU employees have the responsibility to be well informed about risks associated with physical, chemical, and biological hazards in their lab.

1.2 CHEMICAL HYGIENE PLAN SCOPE AND APPLICATION

This document serves as a guide for FSU compliance with the MIOSHA Hazardous Work in Laboratories Standard and the Chemical Hygiene Plan requirements. All programs and facilities at FSU engaged in the laboratory use of hazardous materials are required to comply with this document.

The primary objective of this Plan is to provide general guidelines for handling hazardous materials in laboratories. The Plan establishes basic safety principles for laboratory procedures, equipment, and work practices capable of protecting employees from laboratory hazards.

Where the scope of hazards are not adequately addressed by this general document, specific Standard Operating Procedures (SOPs) and safety practices will be developed. Additionally, as programs expand and faculty and staff revise academic programs, this document will be updated accordingly.

This Plan does not apply to:

1. Work with chemicals or biological materials that do not meet the criteria to be considered hazardous by the MIOSHA Hazardous Work in Laboratories Standard. The definition of a hazardous material can be found in the Glossary of Terms in the appendix.
2. Work with chemicals or biological materials that create no risk of exposure to employees.

This document will be referred to as *FSU's Lab Safety and Chemical Hygiene Plan* (The Plan).

1.3 ROLES AND RESPONSIBILITIES

FSU Director of Safety, Health, Environment and Risk Management (SHERM): The FSU Director of SHERM is responsible for the development and implementation of institutional procedures for the establishment and maintenance of an environmentally healthy and safe workplace. The Director of SHERM and Chemical Hygiene Officer serve as resources for compliance with the Plan.

Chemical Hygiene Officer (CHO): Unless otherwise appointed, the CHO functions will be covered by SHERM (Director or designee) along with the academic unit building safety officers or designees, for overall compliance with the Plan. The CHO can delegate responsibility to others, as necessary, to implement and carry out the provisions of the Plan.

The Radiation Safety Officer (RSO) is responsible for compliance with state and federal requirements for using ionizing and non-ionizing radiation, including personnel monitoring. In each laboratory where ionizing and/or non-ionizing radiation is used, there will be an FSU employee who is responsible for

certain essential functions to assure regulatory compliance and the safety of those using radiation. The Radiation Safety Officer is appointed by the Provost and is authorized by the Radiation Safety Committee and its Radiation Safety Handbook.

The Biosafety Officer (BSO): is responsible for compliance with state and federal requirements for using infectious agents or biologically hazardous materials. The CHO serves as the BSO at FSU.

Laser Safety: The Director of SHERM is responsible for approval of procurement and safe operation of class 3b and 4 lasers. Please contact the Director of SHERM for questions about laser use on campus.

FSU Department of Public Safety will, with the assistance of Physical Plant, coordinate response activities in the event of an emergency. Physical Plant is responsible for operational safety.

Health and Safety Committee (HSC) is comprised of faculty and staff that are charged by the Dean to provide management for the Safety Plan. New projects, expanded use of hazardous chemical and biological materials, and/or physical hazards which pose unusual or uncontrollable risks shall be reviewed and approved by the CHO.

University Employees whose job responsibilities are laboratory-based (teaching or research) are responsible for being familiar with the safe practices and requirements of the Plan and building-specific health and safety procedures. Non-laboratory based University employees who work with hazardous materials are responsible for being familiar with the practices and requirements of the FSU Hazard Communication Program. All individuals performing work with hazardous substances must accept a shared responsibility for working in a safe manner once they have been informed about the extent of risk and safe procedures for their activities. They also have the responsibility to inform supervisors or safety personnel of accidents and work practices or conditions that they believe to be hazardous.

Academic Deans and their designees are responsible for the overall safety and well-being of faculty, staff, and students and shall make available the resources necessary to carry out the provisions of the Plan.

Faculty will ensure that students and staff complete required chemical and lab safety training at the beginning of each course or research project in which hazardous materials are used. The training will be documented as appropriate (see section 2.0 below). Lab-specific safety training will be provided at the beginning of each class period on an as-needed basis.

Lab Supervisors, departmental and research, have the responsibility for the safety and well-being of all persons in contact with any university-related activity utilizing radiation, chemical, or biological hazards. Lab supervisors include any faculty or staff member running a research project that involves hazardous materials as well as departmental lab supervisors as defined in the FSU job description. Specifically, the lab supervisor is responsible for;

1. Ensuring that all employees under his/her supervision have received FSU laboratory safety training,
2. Providing all employees under his/her supervision with site-specific training and documenting such training,
3. Following procedures prescribed in this document, and in department or site-specific plans.

1.4 EMPLOYEE RIGHTS

It is the employee's right to receive information about the known physical and health hazards of the hazardous materials in their work areas and receives adequate training to work safely with these substances. Employees have the right to work in a safe environment and inform the laboratory supervisor about potential risks in the laboratory (per MIOSHA part 431 – Hazardous Work in Laboratories).

1.5 PLAN AVAILABILITY

The Plan is available for all COP faculty and staff, accessible via the College website.

1.6 ANNUAL REVIEW

It is the responsibility of the COP HSC to review the Plan annually from its effective date and make any necessary modifications as programs, courses, and/or projects change.

2.0 TRAINING

Employees will have access to information and training to ensure that they are informed of the hazards of materials present in their work area. Such information will be provided at the time of an employee's initial assignment to a work area where hazardous materials are present and prior to assignment involving new exposure situations. Employees will receive periodic refresher information and training to ensure that they are aware of the risks of exposure to hazardous materials.

2.1 GENERAL AWARENESS TRAINING

General awareness training will be provided by the CHO or other instructor and will include:

1. The content of MIOSHA's Hazardous Work in Laboratories Standard and the location of the Plan.
2. A description of permissible exposure limits for certain OSHA/MIOSHA regulated substances.
3. How to identify signs and symptoms associated with exposures to hazardous chemicals used in the laboratory (available on Safety Data Sheets).
4. Methods and observations that may be used to detect the presence or release of a hazardous material (such as monitoring conducted by continuous monitoring devices, visual appearance, or odor of hazardous chemicals when being released, etc.).
5. General physical and health hazards of chemical or biological material in the work area. This must include an awareness that many factors influence whether a given material might constitute a hazard (e.g., dose, exposure time, users' genetic background or developmental state, mixtures of interactions of chemicals, etc.).
6. The measures employees can take to protect themselves from these hazards, including specific procedures the University or department has implemented to protect employees from exposure to hazardous chemicals, such as appropriate work practices, emergency procedures, and personal protective equipment to be used.
7. The location and availability of known reference materials on the hazards, safe handling, storage, and disposal of hazardous materials found in the laboratory, including, but not limited to, Safety Data Sheets (SDS) received from the supplier.

2.2 LABORATORY-SPECIFIC TRAINING

Training on hazards specific to a task or area shall be provided to employees by lab supervisors or faculty and includes:

1. Site-specific emergency procedures
2. Site-specific standard operating procedures.

3. Specific physical and health hazards of materials in the work area (available on SDS).
4. Methods to prevent exposure of identified hazards and personal protective equipment.
5. Descriptive information on the function and use of general and local exhaust ventilation that serves the lab(s) in use.

2.3 METHOD OF TRAINING

Training will be provided by the CHO, or other knowledgeable faculty, staff, or outside consultant, and may take the form of individual instruction, group seminars, audiovisual presentations, handout material, computer-based learning management programs, or any combination of the above. Site-specific training will be provided by Lab Supervisors or knowledgeable and qualified faculty.

Signing the course-sign-in and/or completing the online quizzes, acknowledges that employees understand the FSU Plan and the policies and procedures applicable to the MIOSHA Laboratory Standard and will work in compliance with those policies. In addition, the training session you have attended includes applicable health and safety related policies and procedures as explained by the instructor. The appropriate Lab Supervisor will provide additional laboratory-specific training on an as-needed basis.

2.4 RECORD KEEPING

General awareness training required by the Plan will be documented by the CHO. Records will either consist of a Record of Training form or the Learning Management System (LMS) attendance or online completion records. For training completed on FSU's LMS, the grade book replaces the "record of training" since a login is the equivalent of a signature, and the results of the quiz reflect the level of understanding. The CHO will maintain this documentation. Laboratory-specific training must be documented and maintained by the faculty PI or lab supervisor and shall be available upon request.

The amount of time the CHO chooses to retain training records is not specified in the Laboratory Standard. However, FSU policy is to retain training records for at least one year after an employee leaves a position or student leaves the course. Where applicable, Safety signoffs for specific laboratory class safety policies will be maintained by the Unit or Departmental Laboratory Supervisor.

3.0 STANDARD OPERATING PROCEDURES

This Plan provides certain procedures for health and safety standard operating procedures (SOPs) that apply to laboratory work involving the use of hazardous chemicals, hazardous biological materials, and/or operations with a high degree of risk. SOPs are prepared in order to standardize lab-specific activities, thereby adding a higher level of safety to achieve a predictable outcome. Additional procedures may be necessary for labs with health and safety hazards greater than those presented in The Plan.

3.1 LAB SPECIFIC STANDARD OPERATING PROCEDURES REQUIRED

Principal Investigators and Lab Supervisors must assess the risks and identify hazards associated with working in their area. Once hazards are identified, they must develop, implement, and maintain lab-specific procedures to safely address high hazard materials/processes, and then train laboratory personnel on applicable procedures. In relatively low hazard labs, the procedures outlined in this manual may be sufficient. Faculty and staff may create their own procedures or use publicly available resources such as reference books, internet sites (of a reliable source), or lab manuals.

3.2 GENERAL SAFETY PRINCIPLES

The following guidelines have been established to assist lab faculty and staff in managing potential hazards and in maintaining a basic level of safety. Below are guidelines that establish minimum requirements for those who may use and/or work in labs.

1. Understand the known hazards associated with the materials being used. Never assume all hazards have been identified. Carefully read labels before using an unfamiliar chemical. When appropriate, review the Safety Data Sheet (SDS) for special handling information. Determine the potential hazards and use appropriate safety precautions before beginning any new operation.
2. Be familiar with the location of emergency equipment such as fire alarms, fire extinguishers, emergency eyewash, and shower stations, and know the appropriate emergency response procedures.
3. Avoid distracting or startling other workers when they are handling hazardous materials.
4. Use equipment and hazardous materials only for their intended purposes.
5. Always be alert to unsafe conditions and actions and call attention to them so that corrective action can be taken as quickly as possible.
6. Wear appropriate skin, eye, and face protection.
7. Always inspect equipment for leaks, tears, or other damage before handling a hazardous material. This includes fume hoods, gloves, goggles, etc.
8. Avoid tasting or smelling chemicals.

3.3 HEALTH AND HYGIENE

The following practices have been established to protect laboratory employees from health risks associated with the use of hazardous chemicals:

1. Avoid direct contact with any hazardous material. Know the types of protective equipment required while using any chemical. If in doubt, review the appropriate section of the SDS.

2. Confine long hair and loose clothing and always wear footwear that fully covers the feet.
3. Do not mouth-pipette.
4. Use appropriate safety equipment whenever there is a potential for exposure to hazardous gases, vapors, or aerosols. Check to ensure that local exhaust ventilation equipment is working properly before use. In the event that general or local exhaust ventilation is not functioning properly, immediately stop work, notify Facilities, and place a sign to notify others that work with hazardous materials is suspended until the equipment is working properly.
5. Wash thoroughly with soap and water after handling chemicals or biological materials, before leaving the laboratory and before eating or drinking.
6. If there is a hazardous splash potential, splash goggles shall be worn as eye protection.
7. Clean and store personal protective equipment as appropriate.
8. Laboratory employees shall be familiar with the signs and symptoms of exposure for the materials with which they work and the precautions necessary to prevent exposure.

3.4 FOOD AND DRINK IN THE LABORATORY

1. Avoid eating, drinking, smoking, or applying of commercial products in any laboratory area where hazardous chemicals or biological hazards are in use.
2. Refrigerators and microwave ovens used for chemical or biological storage or other laboratory use shall not be used for food storage or preparation.
3. Food or beverages for research or experimental purposes should be labelled as such or with the words “not for human consumption”.
4. Use of food, drink and the application of cosmetics are only permitted in rooms where chemical, biological or radioactive materials are not used or stored and have been properly decommissioned to allow such use. In labs where very few low-hazard chemicals are used, an exemption from the food/lab policy may be granted. Designation of a laboratory as acceptable for consumption or storage of food or drink must be approved by the Chemical Hygiene Officer.

3.5 HOUSEKEEPING

Safety follows good housekeeping practices. The following guidelines can be used to maintain an orderly laboratory: Custodians are not to clean up chemicals or biohazards.

1. Keep work areas (including floors) clean and uncluttered. Clean up work areas after the work is finished or at the end of each lab or workday.
2. Dispose of waste per the FSU disposal policies described in Section 6 or the building-specific plan. A separate receptacle must be designated for non-contaminated glass. Contaminated glass is considered hazardous waste and disposed of accordingly.
<https://www.ferris.edu/HTMLS/administration/buspolletter/Bpl0204.htm>
3. Clean spills immediately and thoroughly, as per the guidelines in this document and the product SDS. Ensure a chemical spill kit is available. Faculty, staff, and students should receive training on the proper procedures of cleaning a spill and a designated employee shall assure that the spill kits are properly stocked.

4. Do not block exits, emergency equipment or controls. Do not use hallways and stairwells for storage.
5. Assure hazardous chemicals are properly segregated into compatible categories (section 5.1.4).
6. Custodial responsibilities are limited to sweeping the floors except when chemicals and biological materials are present and emptying the trash.

3.6 HAZARDOUS MATERIALS HANDLING AND STORAGE

Information on proper handling, storage, and disposal of hazardous materials and access to related SDSs are available to all laboratory employees at ferris.msdssoftware.com or by contacting the CHO. Always purchase the minimum amount necessary to maintain operations.

1. Chemical containers with missing or defaced labels should not be accepted.
2. Chemicals utilized in the laboratory or hood must be appropriate for the type and capacity of the ventilation system.
3. Hazardous biological materials should be manipulated using safety equipment and techniques appropriate to the risk group and the evaluated biosafety level of the specific experimental conditions. Biosafety cabinets used to protect researchers from biological hazards must be functioning properly, certified annually and appropriate to the biological and chemical hazards in use.
4. Hazardous materials should be stored in appropriate safety cabinets, closed cabinets or not more than five feet above the floor.
5. Chemicals shall be segregated by compatibility.
6. Hazardous material storage areas must be labeled as to their contents (section 5.1.4)
7. Storage of hazardous materials at the lab bench or work area shall be kept to a minimum.
8. A Hazardous material mixture shall be assumed to be as toxic as its most toxic component.
9. Substances of unknown toxicity shall be assumed to be toxic.
10. Each lab must maintain an inventory of all chemicals along with a Safety Data Sheet (SDS) for each chemical. The SHERM office maintains the online SDS database including location information at: <https://ferris.msdssoftware.com/>.

3.7 TRANSFERRING OF HAZARDOUS MATERIALS

When transporting hazardous materials outside the laboratory, precautions should be taken to avoid dropping or spilling them.

1. Carry glass containers in bottle carriers or other leak resistant, unbreakable secondary containers.
2. When moving hazardous materials on a cart, use a cart suitable for the load and with raised edges to contain leaks/spills.
3. No hazardous waste shall be transported between buildings.

3.8 COMPRESSED GASES

Special systems are needed for handling materials under pressure. Cylinders pose mechanical, physical and/or health hazards, depending on the compressed gas in the cylinder.

1. Cylinders with regulators must be individually secured. Only cylinders with valve protection caps securely in place may be safely gang-chained (chained in groups).
2. When storing or moving a cylinder, have the valve protection cap securely in place to protect the stem.
3. Cylinders must be secured in an upright position at all times. Use suitable racks, straps, chains, or stands to support cylinders against an immovable object, such as a bench or a wall, during use and storage. Do not allow cylinders to fall or lean against one another.
4. Use an appropriate cart to move cylinders.
5. Never bleed a cylinder completely empty. Leave a slight pressure to keep contaminants out.
6. Oil or grease on the high-pressure side of an oxygen cylinder can cause an explosion. Do not lubricate an oxygen regulator or use a fuel gas regulator on an oxygen cylinder. Use an oxygen approved regulator.
7. Always wear goggles or safety glasses with side shields when handling compressed gases.
8. Use appropriate gauges, fittings, and materials compatible with the particular gas being handled.
9. When work with a toxic, corrosive, or reactive gas is planned, the CHO should be contacted for information concerning specific handling requirements. Generally, these gases will need to be used and stored with local exhaust ventilation such as a lab hood or a gas cabinet designed for that purpose.
10. Outside contractors/suppliers have been hired to exchange empty cylinders with full ones. Faculty and staff should limit moving cylinders, but when necessary, use the cylinder restraint cart.

3.9 UNATTENDED OPERATIONS

At times, it may be necessary to leave a laboratory operation unattended. Follow these basic guidelines in the design of an experiment or project to be left unattended:

1. Check with your laboratory supervisor to determine if the operation can be left safely unattended.
2. If the operation is to be left unattended for extended periods and involves hazardous materials or potentially hazardous conditions, develop a protocol. It should be reviewed by the laboratory supervisor and CHO. The protocol should include responses to potential interruptions in electric, water, inert gas and other services and provide containment for hazardous materials.
3. A warning notice must be posted near the experiment if hazardous conditions are present. This notice must contain information concerning the hazard such as indicators of problems and who to contact if such evidence is present.

3.10 WORKING ALONE

Working alone, whether after-hours or in isolation, should be avoided whenever possible. If it becomes necessary to conduct work alone in a laboratory, workshop, or in the field, the Principal Investigator or Lab Supervisor must specify the conditions under which working alone will be permitted.

1. In no case is working alone permitted during procedures involving highly hazardous or toxic chemicals or agents and/or dangerous equipment or environments (i.e.: anything that could cause severe injury or death).
2. It is the responsibility of the Principal Investigator or Lab Supervisor, with support of FSU safety staff, to assess activity of high and low or moderate risk, and develop policies and procedures appropriate for each type of work. It is preferable that departmental staff collaborate on common procedures, processes and equipment for consistency with individual policies. See the FSU Working Alone Policy located at:
https://ferris.edu/HTMLS/administration/academicaffairs/Laboratory_Safety/pdfs-docs/WorkingAlone-clean.pdf

3.11 VOLUNTEERS AND GUEST SCHOLARS IN LABS

Individuals wishing to conduct research for the benefit of the university, but with no compensation, will fall into one of the following categories:

1. **Laboratory Volunteer.** Volunteers in the lab include any unpaid individual who performs services directly related to the business of the university. Volunteers must be working under direction of a Principal investigator or laboratory supervisor. Volunteers must be approved by the department Chair.
2. **Guest Scholar.** Visiting scholars, visiting research professors, and visiting exchange professors working in laboratories, sponsored by faculty and approved by a College Dean are considered guests of the University. They may visit for a temporary period and may not perform in the role of an employee at FSU.

Volunteers and guest scholars are subject to the provisions of this Plan and the following requirements:

1. Any volunteer or guest conducting lab work must be provided with written documentation including, but not limited to the following:
 - a. Review the *Access to Laboratories by Non-FSU Individuals Policy*, and the *Parental Consent Form* (if necessary) available on the AALDS website:
https://ferris.edu/HTMLS/administration/academicaffairs/Laboratory_Safety/Laboratory-Changes/non-fsu_individuals.htm.
 - b. A clearly defined scope of work and disclosure of significant hazards.
 - c. Instructions to complete safety training prior to working in the lab.
 - d. Guest Scholars must have a signed approval letter from the Dean, *Laboratory Use Agreement*, a background check, completed volunteer consent (See Appendix L), and possibly other documentation as required by the Office of Research and Sponsored Programs Compliance Officer. Contact the AALSD for more information.

3.12 LABORATORY SECURITY

Laboratories must be secured using reasonable measures to prevent against theft, unauthorized entry, and misuse of chemicals or equipment, especially those that could present a risk to the public or be used for illicit purposes.

1. Laboratory Personnel Responsibilities: For research labs, Principal Investigators are responsible for the security of their laboratories. In teaching labs, the Department Chair is responsible for chemical and equipment security. All laboratory staff and students should take the following precautions:
 - a. Be aware of unfamiliar individuals in restricted areas. Either approach them to inquire as to their purpose in the area (“can I help you?”) or report to faculty or staff.
 - b. Report suspicious behavior and security problems to Public Safety.
 - c. Ensure doors from public access areas into restricted access areas remain locked. Do not prop doors open.
 - d. Do not provide access to unfamiliar individuals.
 - e. Keep accurate inventories of chemicals and equipment.
 - f. Do not leave hazardous materials or valuable equipment unsecured.
 - g. Properly dispose of unwanted chemicals.
2. Laboratory Access: Faculty, staff and students will be provided with access cards or brass keys upon approval by the Department Chair or Dean of the College, or their designee. Keycard or keycode restrictions are as follows:
 - a. Academic departments and/or the Dean of the College will determine individuals who are authorized to request issuance of a keycard. The individual making request shall maintain a record of all cards and names that they have been assigned to. In the event of a lost/stolen keycard, the authorized individual shall have the card cancelled immediately.
 - b. Faculty and staff cards/codes will be deactivated upon request of the Department Chair or termination of employment. Student cards will be issued for a term not longer than one year, at which time the authorized individual must request an extension.
 - c. PI’s may request any access times for student cards during typical building operating hours without prior approval. Additional access will be granted upon demonstration of established policies for after-hours access. PI’s requesting after-hours access for their research staff must provide the Chemical Hygiene Officer with:
 - i. Identification of the room/space where access is being requested.
 - ii. A description of lab work and potential hazards, if any.
 - iii. Specific policies for working alone in the space.
 - d. Access to certain restricted areas, such as the shop, those using radiation, level 2 biohazards, and laboratory animals will only be granted upon approval by both the Department Chair and that program’s designated university official. Each individual entering such areas must swipe his or her card on the reader, unless access is part of a class or the individual is directly supervised by the Principal Investigator.
 - e. Do not allow unknown individuals into key-carded areas. Cardholders are responsible for the actions of any individuals that they allow into a secure area.

4.0 CHEMICAL HANDLING & STORAGE REQUIREMENTS

4.1 HAZARD IDENTIFICATION

At a minimum, hazardous material containers must have the chemical name(s) and hazard identification(s). With respect to identifying containers, storage areas and laboratory entranceways, the following guidelines should be followed. These responsibilities can be delegated to someone who has received adequate training but the ultimate responsibility lies with the lab supervisor and faculty/staff who are using or directing the use of the material.

1. Labels on incoming containers of hazardous materials for laboratory use may not be removed or defaced. Labels contain information on the identity and the hazards associated with the material. It is recommended that incoming containers be labeled with the department or user name and date received.
2. Laboratory containers must be labeled (i.e.: bottles filled from the original container, see section 3.2.1.).
3. Hazardous material storage areas must be labeled per the guidelines established in section 5.1.4.
4. Entranceways to laboratory facilities must be labeled with the appropriate warning signs per the guidelines established in section 5.1.2.
5. All employees must have access to Safety Data Sheets (see section 5.1.1.)

4.2 LABELING

All containers must be labeled with the name of the contents and the hazard(s), if not provided by the manufacturer. If a material has more than one hazard, it must be labeled with both hazards. No hazardous chemicals and/or substances will be accepted for use at Ferris State University, or shipped to any other location unless they are clearly labeled with the following information:

1. The identity of the hazardous material and proper safety precautions
 - a. For containers labeled by the manufacturer:
 - i. Inspect the labeling on incoming containers.
 - ii. Replace damaged or semi-attached labels.
 - b. For transferred products or prepared solutions labeled by the user:
 - i. Label each chemical container with the chemical name and hazard warning
 - ii. Refer to the SDS for hazard warning
 - c. For Labeling Multiple Small Containers using Legend Method
 - i. Label containers with abbreviated chemical name and a hazard warning.
 - ii. Provide a key in a visible location in the lab with complete chemical name.
 - iii. Document that employees are trained on the labeling system
 - d. For labeling multiple small containers using the box or tray method:
 - i. Put containers in box or tray.
 - ii. Label tray with chemical name and hazard warning
 - iii. If containers are removed from the box/tray, they must be properly labeled or returned to the box or tray within the work-shift.
 - e. Peroxide Forming Chemicals must be labeled with: Date received, opened, tested, and results.
2. The appropriate hazard warnings as outlined in the Federal Right to Know Standard or the Global Harmonization System.

- a. All hazardous chemical labels must be clearly legible and prominently displayed on the container
- b. If the chemical in question is subject to any special regulatory provisions - such as Michigan class "A" carcinogen, then said chemical must be labeled in accordance with the provision.
- c. In work situations involving stationary process containers or any process that might create a health hazard during the normal completion of a given task (welding, for instance) the label can be replaced by a sign, placard or batch ticket indicating the identity and nature of the hazard. These warnings must be readily visible to employees.
- d. Any portable vessel containing hazardous chemicals that will not be used on the work shift during which the container was filled, must be labeled with the appropriate hazard information.
- e. No label may be removed or defaced unless a substitute is immediately provided. Employees must not remove or deface any label without express consent from a supervisor or appointed Chemical Hygiene Officer. The OSHA Compliance Directive states that, before any product can be used, the proper label must be present. Any container without a label should be reported by the employee to his/her supervisor.
- f. The identity on the container label must read exactly as it does on the Safety Data Sheet. If a trade name is used on the SDS, then a trade name should be on the label. If the chemical name is used on the SDS, then the container should be labeled accordingly.
- g. Anything available over the counter as a "consumer product" to the public is exempt from labeling requirements if it has already been labeled by the manufacturer and the label is intact.

4.3 CHEMICALS DEVELOPED IN THE LABORATORY

The following requirements apply to chemical substances produced in the laboratory:

1. If the composition of the chemical substance that is produced exclusively for the laboratory's use is known, the lab supervisor must determine if it is a hazardous chemical. If the chemical is determined to be hazardous, the lab supervisor must provide appropriate training to protect employees and provide a written procedure for handling, use, and disposition of the chemical compound.
2. If the chemical produced is a product or a by-product whose composition is not known, the lab supervisor must assume that the substance is hazardous and must comply with the requirements of the Plan.
3. If the chemical is produced for sale or use outside of the laboratory, the lab supervisor must prepare an appropriate SDS in accordance with Michigan's Right-to-Know Law.

4.4 HAZARDS SUBJECT TO REVIEW OR PRIOR APPROVAL

All academic and research activity with potential exposure to hazardous chemicals, biological agents, equipment, or work areas is subject to review by the CHO. It is the responsibility of the CHO and faculty/staff to evaluate hazards and identify lab activities that are sufficiently hazardous as to cause or have a significant potential to cause injury to employees and/or students. As a guide (and as a minimum), the activities discussed in the MIOSHA lab standard shall be reviewed and assessed for personnel exposure.

If the CHO's or faculty/staff hazard assessment identifies high risk operations that cannot be eliminated or controlled, the CHO and/or Lab Safety Committee must provide approval. Additional hazard

assessments will be conducted by the responsible faculty member annually for procedures that have expanded in scope or increased potential hazards.

4.5 PROVISIONS FOR PARTICULARLY HAZARDOUS SUBSTANCES

1. Permissible Exposure Limits.

The Laboratory Standard requires that employers, for laboratory uses of substances regulated by OSHA/MIOSHA, assure that employees' exposures do not exceed the Permissible exposure Limits (PELs). The PELs represent Time Weighted Averages (TWA's) in parts per million (ppm) or milligrams of substance per cubic meter of air (mg/m³). The TWA represents the ratio between exposure and work shift. PELs can be found in the Occupational Health Standard Part 301 of Michigan's Department of Labor and Economic Growth. An additional reference is the American Conference of Governmental Industrial Hygienists (ACGIH) has established Threshold Limit Values (TLV's), which are TWA values similar to the PEL's. Refer to the SDS or MIOSHA's web site for exposure limits and related information.

See Appendix for FSU's Respiratory Protection Program

2. Employee Monitoring

Faculty/Staff or the CHO must perform employee exposure monitoring under the following circumstances:

- a. Initial monitoring must be performed if there is reason to believe employee exposure levels routinely exceed the action level, or PEL.
- b. Periodic monitoring must be performed when initial monitoring reveals an exposure. The employer must comply with exposure monitoring provisions of the relevant standard.
- c. Employers must notify the employee of the monitoring results within 15 working days after receipt of monitoring results. Records of exposure monitoring data should be retained with employee training records indefinitely. Records of exposure monitoring should also be emailed to the University Safety Manager if the employee has been exposed above the action level or PEL.

3. Special Considerations.

The MIOSHA Laboratory Standard requires that special precautions for additional employee protection be followed for the laboratory use of select carcinogens, reproductive toxicants, and chemicals with a high degree of acute and chronic toxicity. Protection from these hazards is provided by assuring exposure to such hazards is minimized or eliminated. To minimize exposure, it is necessary to determine the route by which exposure may occur, whether by inhalation, absorption, injection, ingestion or a combination of exposure routes. To ensure employees do not receive exposures in excess of the PEL, hygienic standards have been established for many toxic materials. The following general hygiene standards should be observed when using select carcinogens, reproductive toxicants, and chemicals with a high degree of acute and chronic toxicity.

1. Establish a designated area.

- a. Use and store materials only in designated areas such as a restricted access hood, glove box, or portion of a lab designated for use of highly toxic substances. Assure that all personnel with access are aware of necessary safety precautions and engineering controls are adequate.

- b. Label all containers, storage and use areas appropriately. Follow the guidelines established in section 3.4.1 of this document.
2. Use proper containment devices for the protocol and chemical(s) being used.
 - a. Use a hood or other containment device for procedures which may result in the generation of aerosols or vapors.
 - b. It is recommended that breakable containers be stored in chemical-resistant trays. Work and mount apparatus above such trays or cover work and storage surfaces with removable, absorbent, plastic backed paper.
3. Remove contaminated waste in accordance with FSU waste disposal guidelines.
4. Follow decontamination procedures prior to leaving the designated area.
 - a. Before leaving the designated area, remove protective apparel. Place it in an appropriate, labeled container. Thoroughly wash hands, forearms, face, and neck.
 - b. Thoroughly decontaminate or dispose of contaminated clothing or shoes. If possible, chemically decontaminate by chemical conversion to a less toxic product.
 - c. Decontaminate vacuum pumps or other contaminated equipment, including glassware, before removing them from the designated area. Decontaminate the designated area before normal work is resumed.
 - d. Use a wet mop or a vacuum cleaner equipped with a HEPA filter to decontaminate surfaces contaminated with particulates. DO NOT DRY SWEEP.
 - e. Protect vacuum pumps against contamination with scrubbers or HEPA filters and vent effluent into the hood.
5. Always take extra precautions when working with particularly hazardous substances.
 - a. Consult the SDS for toxic properties and follow the specific precautions and procedures.
 - b. Guard against spills and splashes. Appropriate safety apparel, especially gloves, should be worn. All hoods, glove boxes, or other essential engineering controls should be operating properly before work is started.
 - c. Notify the Lab Supervisor immediately of all incidents of exposure or spills.

4.6 PROVISIONS FOR PHYSICAL HAZARDS OF CHEMICALS

Physical hazards of chemicals are provided below. User must take certain precautions to avoid personal injury or property damage. Additionally, users should understand chemical incompatibilities and avoid storage or mixing practices that may cause a violent reaction or a toxic gas.

4.6.1 Flammable/Combustible Material

The National Fire Protection Agency (NFPA) places flammable and combustible liquids in the following classes:

*Flash Point is defined as the minimum temperature at which a liquid gives off vapor in sufficient concentration to form an ignitable mixture with air near the surface of the liquid.

Flammable	Flash Point*	Boiling Point
Class IA	< 73°F (22.8°C)	< 100°F (37.8°C)
Class IB	< 73°F (22.8°C)	≥100°F (37.8°C)
Class IC	≥73°F (22.8°C) <100°F (37.8°C)	
Combustible		
Class II	≥100°F (37.8°C) & < 140°F (60°C)	
Class IIA	≥140°F (60°C) & < 200°F (93°C)	
Class IIIB	≥200°F (93°C)	

For handling flammable/combustible materials, observe the following guidelines:

1. Eliminate ignition sources such as open flames, hot surfaces, sparks from welding or cutting, operation of electrical equipment, and static electricity.
2. Store in NFPA approved flammable liquid containers or storage cabinets, in an area isolated from ignition sources or in a special storage room designed for flammable materials.
3. Ensure there is proper bonding and grounding when it is required, such as when transferring or dispensing a flammable liquid from a large container or drum. Assure bonding and grounding is checked periodically.
4. Assure appropriate fire extinguishers and/or sprinkler systems are in the area.
5. No storage of flammable chemicals in container sizes greater than 1 gallon will be permitted in labs unless:
 - a. The flammable chemicals are stored in a flammable storage cabinet
 - b. The flammable chemicals are stored in an approved flammable safety can.
6. Maximum quantity of flammable chemicals in a lab should not exceed 10 gallons of flammable chemicals, unless stored in a safety can or inside flammable storage cabinets.

4.6.2 Corrosives

Corrosives are materials which can react with the skin causing burns similar to thermal burns, and/or which can react with metal causing deterioration of the metal surface.

1. Containers and equipment used for storage and processing of corrosive materials should be corrosion resistant.
2. Eye protection and rubber gloves should always be used when handling corrosive materials. A face shield, rubber apron, and rubber boots may also be appropriate, depending on the work being performed.
3. Never add water to acid. When mixing concentrated acids with water, add the acid slowly to water.
4. An eyewash and safety shower must be readily accessible to areas where corrosives are used and stored. In the event of skin or eye contact with corrosives, immediately flush the area of contact with cool water for 15 minutes. Remove all affected clothing. Obtain medical help. See section 5.3, "Personal Protective and Safety Equipment" for eyewash and safety shower specifications.

4.6.3 Oxidizers

Oxidizers are materials that react with other substances by giving off electrons and undergoing reduction. This reaction may result in fire or explosion. The intensity of the reaction depends on the oxidizing-reducing potential of the materials involved. Know the reactivity of the materials involved in the experiment or process. Ensure there are no extraneous materials in the area that could become involved in a reaction. If the reaction is anticipated to be violent or explosive, use shields or other methods for isolating the materials or the process.

4.6.4 Water Reactive Materials

Water Reactive Materials are materials that react with water to produce a flammable or toxic gas and heat or other hazardous condition. Often a fire or explosion results. Safe handling of water reactive materials will depend on the specific material and the conditions of use and storage. Examples of water reactive chemicals include alkali metals such as lithium, sodium, and potassium, acid anhydrides, and acid chlorides.

4.6.5 Pyrophoric Materials

Pyrophoric Materials are materials that ignite spontaneously upon contact with air. Often the flame is invisible. Examples of pyrophoric materials are silane, silicon tetrachloride, and white or yellow phosphorous. Pyrophoric chemicals should be used and stored in inert environments, and dated when received and opened.

4.6.6 Peroxidizable Chemicals

Peroxidizable Chemicals (Organic Peroxides) are materials which undergo auto-oxidation (a reaction with oxygen in the air) to form peroxides which can explode with impact, heat, or friction. Since these chemicals may be packaged in an air atmosphere, peroxides can form even though the container has not been opened, necessitating careful handling. Date all peroxidizables upon receipt and upon opening. Dispose of or check for peroxide formation after the recommended time depending on the chemical. See Appendix – Common Peroxide Forming Chemicals and Protocol for Detection and Inhibition of Peroxides. Do not open any container that is deformed or has obvious solid formation around the lid.

4.6.7 Light Sensitive Materials

Light-Sensitive Materials are materials that degrade in the presence of light, forming new compounds that can be hazardous, or resulting in conditions such as pressure build-up inside a container that may be hazardous. Examples of light sensitive materials include chloroform, tetrahydrofuran, ketones, and anhydrides. Store light-sensitive materials in a cool, dark place in amber colored bottles or other containers that reduce or eliminate penetration of light.

4.6.8 Unstable Materials

Unstable Materials are compounds that can spontaneously release large amounts of energy under normal conditions, or when struck, vibrated, or otherwise agitated. Some chemicals become increasingly shock-sensitive with age. Of great concern in the laboratory is the inadvertent formation of explosive or shock-sensitive materials such as peroxides, perchlorates (from perchloric acid), picric acid, and azides.

1. Contact the CHO when it is suspected that the inadvertent formation of shock-sensitive materials in ductwork, piping, or chemicals being stored has occurred.
2. Date all containers of explosive or shock-sensitive materials upon receipt and when opened.
3. Store containers of shock sensitive or explosive materials in unbreakable secondary containers, away from heat and direct sunlight.
4. If there is a chance of explosion, use barriers or other isolation methods.

4.6.9 Cryogenics

Cryogenics are liquefied gases that can condense oxygen from the air to create an oxygen rich atmosphere in the nitrogen solution; increasing the potential for fire if flammable or combustible materials are present. Asphyxiation and container over-pressurization are significant hazards due to the large expansion ratio from liquid to gas (700 to 1). Many materials become brittle at extremely low temperatures. Brief contact with materials at extremely low temperatures can cause burns similar to thermal burns. Some of the hazards associated with cryogenics are fire, pressure, weakening of materials, and skin or eye burns upon contact with the liquid.

1. Equipment should be kept clean, especially when working with liquid or gaseous oxygen.
2. Gases or fluids should be controlled to prevent formation of flammable or explosive mixtures.
3. Always wear safety glasses with side shields or goggles when handling. If there is a chance of a splash or spray, a full-face protection shield, an impervious apron or coat, cuffless trousers, and high-topped shoes should be worn. Watches, rings, and other jewelry should not be worn. Gloves should be impervious and sufficiently large to be readily thrown off should a cryogen spill. Potholders could also be used.
4. Containers and systems containing cryogenics should have pressure relief mechanisms.
5. Containers and systems should be capable of withstanding extreme cold without becoming brittle.
6. Since glass ampoules can explode when removed from cryogenic storage if not sealed properly, storage of radioactive, toxic, or infectious agents should be placed in plastic cryogenic storage ampoules. Reheat cold sample containers slowly.

4.7 IONIZING AND NON-IONIZING RADIATION AND RADIOACTIVE MATERIAL

The use of radioactive materials and equipment that produces ionizing and non-ionizing radiation at FSU is strictly controlled by the Radiation Safety Officer. Faculty and staff working in the Medical Imaging and Radiation Sciences Department and sciences that involve the use of radioactive materials are required to follow the safety practices documented in the respective Plans and FSU's Radiation Safety Manual. If there are any questions regarding the information or requirements of working in the area, contact FSU's Radiation Safety Officer (RSO).

4.8 BIOLOGICAL MATERIAL HAZARDS

Use of biological materials at or above Biosafety Level 2 and other potentially infectious agents at FSU is covered by the university's Biosafety Manual. Policies and Procedures are enforced by the Biosafety Officer and the Institutional Biosafety Committee. The current definition of Biological Risk Groups and Biosafety Levels are found in the CDC / NIH Guideline Biosafety in Microbiological and Biomedical Laboratories'. Contact the Biosafety Officer if you plan to use biological materials at or above Biosafety Level 2 or potentially infectious agents.

5.0 LABORATORY FACILITY REQUIREMENTS

5.1 IDENTIFICATION OF HAZARDS

Labels and warning signs should alert employees to potentially hazardous materials and allow those unfamiliar with the laboratory surroundings to identify hazardous chemical use and storage areas, safety facilities, emergency equipment, exits, and aid emergency response personnel. (Signs and labels are generally available from the CHO.)

5.1.1 Safety Data Sheets (SDSs).

A Safety Data Sheet (SDS) is a document containing chemical hazard identification and safe handling information and is prepared in accordance with the OSHA Hazard Communication Standard and the Michigan Right-to-Know law. Chemical manufacturers and distributors must provide the purchasers of hazardous chemicals an appropriate SDS for each hazardous chemical/product purchased.

FSU has developed a database of SDS's using chemical inventories from hazardous material users. A link to the database can be found at <https://ferris.msdssoftware.com/>. [TD1][MJM2]

5.1.2 Generic Signs

The following signs have been posted in areas readily accessible. They include:

1. The Michigan Right-to-Know law poster
2. Emergency contact numbers are posted on the doorway leading out into a corridor.

5.1.3 Restricted Access and Designated Areas.

Facilities containing certain hazards must have warning signs posted at the designated area of the laboratory where the hazard exists, and at the entranceway to the laboratory. Any areas placarded as such are restricted access, designated areas, and have certain standards regarding training and use by employees. Such hazards include:

1. MIOSHA carcinogens (see Appendix P or contact CHO if you have questions)
2. HIV and HBV research laboratories and production facilities
3. Biological agents that require Biosafety Level 2 or higher controls
4. Sources of ionizing radiation
5. Radioisotopes and radiolabeled materials
6. Areas with high magnetic fields, UV light, laser usage, or radio frequency generators

Other hazards will be addressed on a case-by-case basis with consultation from the CHO.

5.1.4 Storage Areas.

Chemicals should be stored according to compatibility as designated by hazard classes. Particularly hazardous chemicals should be stored and handled with extreme care. When ordering chemicals that are unfamiliar, request and review the SDS before purchase. To make sure that proper use and storage guidelines are understood. Assure that the following areas are labeled and chemicals are stored appropriately:

1. Carcinogens
2. Corrosives
3. Flammable Liquids
4. Flammable Solids
5. Oxidizers
6. Perchloric Acid
7. Biosafety Level 2 or higher

5.2 CONTROL MEASURES

Control measures must be evaluated required when the following circumstances are met:

1. Whenever employees use hazardous materials.
2. Whenever employee exposures exceed the action level (or, in the absence of an action level, the Permissible Exposure Limit, the published exposure limit or the Threshold Limit Value).
3. Upon addition of new chemicals or changes in procedures.
4. Other situations will be addressed on a case-by-case basis. Please consult the CHO for assistance in establishing the appropriate control measure.

Use the following primary methods for detecting exposures:

1. Determine the source of exposure.
2. Determine the path the contaminant follows to reach the employee
3. Determine the employee's work pattern and use of personal protective equipment.

5.2.1 Administrative Controls

Methods of controlling employee exposures to contaminants by job rotation, work assignment or time periods away from contaminant. Examples include Standard Operating Procedures, Chemical Hygiene Plan, and Safety Manuals.

1. Use training and education as primary administrative controls for reducing exposures.
2. Substitute less harmful chemicals whenever possible.
3. Change or alter processes to minimize exposure.

5.2.2 Engineering Controls

Methods of controlling employee exposures by modifying the source or reducing the quantity of contaminants released into the work environment. Examples include fume hoods, biosafety cabinets and chemical containment.

1. Isolate or enclose a process or work operation to reduce the number of employees potentially exposed (i.e. fume hood, glove box, etc.).
2. Use local exhaust ventilation (hoods) at the point of generation or dispersion of contaminants and use dilution (general) ventilation to reduce air contaminant concentrations.
3. Use wet methods to reduce the generation of dust.
4. Use special control methods such as shielding and continuous monitoring devices to control exposures in special situations.
5. Practice good housekeeping procedures to reduce unnecessary exposures.

Note: MIOSHA R 325.51105 regarding air contaminants, states that engineering controls and administrative controls shall first be determined and implemented when feasible. When such controls are not feasible to achieve full compliance, protective equipment or any other protective measures shall be used to keep the exposure of employees to air contaminants within the limits prescribed in the rule.

5.3 PERSONAL PROTECTIVE EQUIPMENT

FSU will provide necessary engineering controls and safety equipment to all employees to maintain a safe working environment. It is the employee's responsibility to ensure proper use and care of such equipment.

Each lab will assess its operations and hazards, to determine the necessary personal protective equipment (PPE) necessary to adequately protect employees. The lab supervisor or faculty member

is responsible for hazard evaluation, PPE determination, and enforcement of required PPE rules in their lab. In common or prep areas, departmental leaders and faculty are ultimately responsible for ensuring that they follow and enforce PPE requirements. The SDS will provide some information on the PPE and safety procedures recommended for a given chemical, though the SDS may not provide sufficient information concerning the specific type of safety equipment required (for example, it may say "use gloves" but not list the best type of glove to use).

5.3.1 Eye and Face Protection

Eye protection is available to all employees or visitors to laboratories where chemicals are used and stored. Protective eye and face equipment must be used where there is a reasonable probability of injury from hazardous materials that can be prevented from such equipment.

The laboratory supervisor establishes the minimum level of eye protection needed for the laboratory activity. Specialized types of eye protection, such as ultraviolet light restricting safety glasses, are available on an as needed basis. All eye protective devices for laboratory use must be stamped with "Z87" by the manufacturer if they meet ANSI standards. If the eye protection is not marked, it may not meet minimum eye safety protection standards.

1. Safety glasses with side shields offer protection against flying fragments, chips, particles, sand, and dirt. Safety Glasses are the minimum level of eye protection required when an impact hazard exists or when working with hazardous materials. Safety glasses are acceptable when:

- a. Pipeting hazardous materials
- b. Handling closed bottle of hazardous materials
- c. Mixing small quantities of solutions of hazardous materials
- d. Opening centrifuge tubes

2. Safety goggles (impact goggles) offer adequate protection against flying particles. These should be worn when working with glassware under reduced or elevated pressure or with drill presses, grinders or other similar conditions.

3. Chemical splash goggles have indirect venting for splash proof sides, which provide adequate protection against splashes. Chemical splash goggles offer the best eye protection from chemical splashes. Impact goggles should not be worn when danger of a splash exists. Chemical Splash Goggles are required when working with corrosive or injurious chemicals and a reasonable probability of splash exists, for example:

- a. Pouring acid out of a 1 pint bottle
- b. Pouring methylene chloride from a 1 liter bottle
- c. Working with liquids under pressure

4. Face shields protect the face and neck from flying particles and splashes. Always wear additional eye protection under face shields. Ultra-violet lightface shields should be worn when working over UV light sources. Face Shield and Chemical Splash Goggles are required when working with larger quantities of corrosive chemicals or a high probability of eye and face injury exists such as:

- a. Working with an acid bath
- b. Pouring 4 liters of acid into a container
- c. Handling highly reactive chemicals that may spatter

Note: Ordinary prescription glasses do not provide adequate protection against eye injury. Eye protection equipment must be ANSI Z87 approved.

5.3.2 Protection of Skin and Body

Skin and body protection involves the use of protective clothing to protect individuals from chemical exposure. Determine clothing needed for the chemical being used, as protective garments are not equally effective for every hazardous chemical. Some chemicals will permeate a garment in a very short time, whereas others will not.

1. The basic and most effective forms of protection are gloves and lab coats.
2. Protect exposed skin surfaces when there is a reasonable anticipation of a splash.
3. Open toed shoes and sandals are not permitted in labs.
4. Even when there is minimal danger of skin contact with an extremely hazardous substance, lab coats, coveralls, aprons, or protective suits should be utilized. These garments should not leave the lab.
5. Exposures to strong acids and acid gases, organic chemicals and strong oxidizing agents, carcinogens, and mutagens require the use of specialized protective equipment that prevents skin contamination. Impervious protective equipment must be utilized. Examples include rubber gloves, aprons, boots, and protective suits.

5.3.3 Hearing Protection

Hearing protection is required where noise levels exceed OSHA limits. Typically lab environments will not exceed those levels. Contact the CHO for evaluation of high noise areas or operations.

5.3.4 Respiratory Protection

Generally laboratories are provided with fume hoods to prevent situations where respirators would be necessary. See appendix for FSU's Respiratory Protection Policy

5.4 SAFETY EQUIPMENT

5.4.1 Safety Showers

Safety Showers are required to provide an immediate water drench of an affected person. MIOSHA has adopted the following ANSI standards for location, design, and maintenance of safety showers:

1. Showers are located within 25 feet of areas where chemicals with a pH of < 2.0 or > 12.5 are used.
2. Showers are located within 100 feet of areas where chemicals with a pH between 2 and 4 or 9 and 12.5 are used.
3. Shower location is to be clearly marked, well lighted, and free of obstacles, closed doors, or turns.
4. Safety showers are checked and flushed monthly.

5.4.2 Eyewash Facilities

Eyewash Facilities are required in all laboratories where injurious or corrosive chemicals are used or stored and are subject to the same proximity requirements as safety showers. MIOSHA has adopted the following ANSI standards for location, design, and maintenance of emergency eyewash facilities:

1. Optimally, those affected must have both hands free to hold open the eye to ensure an effective wash behind the eyelids. This means providing eyewash facilities that are operated by a quick release system and simultaneously drench both eyes.

2. Eyewash facilities at FSU will provide the minimum of a 15-minute water supply at no less than 0.4 gallons per minute.
3. Eyewash facilities should be checked and flushed weekly. A log documenting flushes is recommended.

5.4.3 First Aid Kits

First aid kits should be readily accessible to all laboratory personnel and should be inspected frequently to ensure that the kit is sufficiently stocked. The kit need only to provide equipment for minor cuts and scrapes.

5.4.4 Spill Kits

Ready access to a spill kit is required in laboratories that work with hazardous materials and employees should be trained on its use. The basic supplies that should be available in a spill kit should be determined by area lab supervisors or faculty based on the hazards of materials used or stored in that area. Contact the CHO or your area Lab supervisor if you want assistance in selecting appropriate spill supplies and PPE.

5.4.5 Fire Extinguisher

Fire extinguishers have been placed in each lab and research space using hazardous materials at FSU. The fire extinguisher in the laboratory should be the appropriate classification type for the expected fire. Type A are used on combustible (wood, paper rubber, plastic) fires, Type B are used on flammable liquid fires, Type C are used on energized electrical equipment fires, and Type D are used on combustible metal (lithium, sodium, magnesium, potassium) fires. Multipurpose (Type ABC and Type BC) extinguishers are also available. SHERM inspects fire extinguishers annually. Physical plant conducts monthly inspections. Notify Public Safety any time a fire extinguisher is discharged. [MJM3]

5.4.6 Telephone and Emergency Contact List

Each laboratory using hazardous chemicals must have convenient access to a telephone or have reliable cellular phone coverage. In addition, each lab must post a list of emergency contact phone numbers.

5.5 LABORATORY VENTILATION

Lab ventilation controls are those controls intended to minimize employee exposure to hazardous chemicals by removing air contaminants from the work site. There are two main types of ventilation controls:

1. General (Dilution) Exhaust: a room or building-wide system that brings in air from outside and ventilates within. Laboratory air must be continually replaced, preventing the increase of air concentration of toxic substances during the workday. General exhaust systems are not recommended for the use of most hazardous chemicals.
2. Local Exhaust: a ventilated, enclosed workspace intended to capture, contain, and exhaust harmful or dangerous fumes, vapors, and particulate matter generated by procedures conducted with hazardous chemicals. These may include fume hoods and biological safety cabinets.

To determine ventilation requirements, review the SDS. Once a local ventilation system is installed in a work area, it must be used properly to be effective. For use of hazardous chemicals warranting local ventilation controls, the following guidelines should be observed:

5.5.1 Fume Hood Safe Work Practices [MJM4][TD5]

1. Conduct all operations that may generate air contaminants at or above the appropriate PEL or TLV inside a fume hood.
2. Do not put your head or upper body into the hood, unless hazardous materials are not present.
3. Hoods should not be used for permanent storage of hazardous materials or equipment. With the exception of certain hazardous waste containers, all chemicals should be stored in an appropriate location outside of the hood.
4. Hazardous materials and equipment should be placed at least six inches inside the hood for proper containment of chemical vapors. Place heat generating equipment to the rear of the hood.
5. Equipment inside the hood should be placed so as to not block airflow through slots in the baffle. Blocks may be necessary under large equipment to allow air to flow to the rear baffle.
6. The fume hood safety-glass sash should be kept below the “stopper” at approximately 18”. In general, the sash height should be set at a level where the operator is shielded to some degree from any explosions or violent reactions which could occur and where optimum airflow dynamics are achieved. If a fume hood has no markings regarding sash height or inspection dates, please contact the CHO to arrange for an inspection.
7. Alarms: Most hoods are equipped with flow sensors. They will generally alarm if flow is too low or too high. Typically the problem corrects itself, possibly after adjusting sash height. If an alarm continues, stop using the hood and contact a Lab Supervisor or Facilities Services. The alarm can be “muted”, however the hood should not be used until the proper flow rate is shown on the monitor.
8. Emergency Purge: In the event of a spill, smoke, or other unintended vapors, press the emergency button on the sensor to increase to maximum fan speed.
9. When not in use the hood should be completely closed to reduce energy consumption.
10. Minimize foot traffic and other forms of potential air disturbances past the face of the hood.
11. Do not have sources of ignition inside the hood when flammable liquids or gases are present.
12. Ensure that air flow is 70 fpm or greater prior to each use to assure that the hood is functioning. Never work with hazardous chemicals or biohazards if the required ventilation system is not working.
13. Hoods should not be routinely used as a waste disposal mechanism for volatile materials.
14. Do not block air supply vents or exhausts in the room.
15. Perchloric Acid Hoods: Use of perchloric acid must be done in a designated hood. Currently perchloric acid use is discouraged at FSU and no hoods have been designated.
16. Always use proper personal protective equipment when working with chemicals in a hood. Hoods are used when a chemical or a procedure has a greater than usual potential is especially dangerous, so eye protection, gloves, and lab coats should be worn.

5.5.2 Biological Safety Cabinet Safe Work Practices

The Biological Safety Cabinets are used to provide containment of infectious splashes or aerosols generated by many microbiological procedures. BSC's use High Efficiency Particulate Air (HEPA) filters to protect personnel and products inside the BSC from contamination from aerosols and particulates. They also protect the laboratory by isolating and containing the work in progress within the BSC. Properly maintained Biological Safety Cabinets are used whenever:

- a. Procedures with a potential for creating infectious aerosols or splashes are conducted. These may include centrifuging, grinding, blending, vigorous shaking or mixing, sonic disruption, opening containers of infectious materials whose internal pressures may be different from ambient pressures, inoculating animals intranasally, and harvesting infected tissues from animals or eggs.
- b. High concentrations or large volumes of infectious agents

Guidance for safe use of biological safety cabinets:

1. Never use chemicals with the potential to generate hazardous vapors. The HEPA filters are intended only to remove particulates and biological agents.
2. Never work in or near the hood with the ultraviolet light turned on. UV light can damage eyes and exposed skin very quickly. Only use the light for the minimum period of time necessary for disinfection, never more than 15 minutes. Note: NIH, CDC, and ABSA all discourage the use of UV for disinfection.
3. Work surfaces should be decontaminated with an appropriate disinfectant on a routine basis, after work with infectious materials is finished, and especially after spills, splashes, or other contamination by infectious materials.
4. If the unit is not left running continuously, turn the blower on and air purge for at least five minutes to remove airborne contamination before the next use.
5. Each laboratory should develop procedures which identify the hazards that will or may be encountered, and which specifies practices and procedures designed to minimize or eliminate risks.
6. Laboratory personnel must receive appropriate training on the potential hazards associated with the work involved, including the necessary precautions to prevent exposures, and the exposure evaluation procedures.

Standards for Inspection: Each user is responsible for ensuring that fume hoods and biological safety cabinets are operating properly prior to use. FSU [KLH6] will conduct at least annual inspections of fume hoods to evaluate the airflow, sash, and overall condition of each hood. Every three years each hood will be certified by a third party inspection contractor. [TD7] BSC's must be certified annually or after repairs. Hoods and BSC's will be posted with date of certification. Notify a CHO or AALSD for operation or maintenance concerns. [MJM8][TD9]

5.6 STANDARD REPAIR / CLOSE-OUT / DECOMMISSIONING PROCEDURES

When a request for equipment repair or transfer to another location is initiated, the following steps must be undertaken to ensure the safety of the employees responsible for repair or transfer if the equipment has been contaminated by hazardous chemicals:

1. Remove chemical contaminants with an appropriate solvent or cleaning solution.
2. Once contaminants have been eliminated, place sign indicating decontamination status in a prominent position on the equipment to be repaired or transferred.

6.0 HAZARDOUS WASTE MANAGEMENT PLAN

Each laboratory has a designated space where hazardous waste is accumulated. All such waste must be collected in the lab in clearly labeled bottles that are tightly capped. It is recommended that waste be reagent/chemical specific, but waste reagents may be mixed if they are of the same category of waste and not capable of reacting with other wastes stored in the same container. When waste is ready for storage, it may be moved to the hazardous waste accumulation area. Follow the procedure found in Unit specific plans for securing and logging the waste in the designated waste area. If present, follow the directions on the door and fill out the log with the category and amount of waste, container type, and date. (Labels are available from the Lab Supervisor.) Transporting of hazardous waste between buildings or campuses shall be according DOT Regulations.

6.1 Waste Characterization

1. Each Principal Investigator or Lab Supervisor lab must identify each waste stream and proper disposal procedures for wastes generated in the lab. University TCD10] SHERM or AALSD staff are available to assist with identification to ensure compliance with waste disposal requirements. MJM11]
2. Each lab must have appropriate containers and waste accumulation areas for waste identified in their lab. Do not place incompatible waste into a single waste container.

6.2 Container Management

1. Waste chemicals accumulated in the laboratory must be placed into containers that are in good condition, compatible with the contents, and able to be closed. Waste containers should be kept clean with no visible contamination on the outside of the container.
2. Waste containers must remain be closed when not adding or removing waste.
3. Waste containers must be labeled with:
 - a) The words “Waste” “Lab Waste” or “Hazardous Waste”
 - b) The name or type of chemical such as “Acetone” or “non-halogenated solvent”
 - c) The date accumulation started and the name of the person or class generating the waste.
 - d) Any other descriptions about the contents pertinent to the disposal facility. Provide as much detail as possible. If “unknown” list any details that might assist with characterizing the waste. MJM12]
4. Areas where waste chemicals are accumulated must have secondary containment sufficient to collect any incidental spills from container failure. Containers should not be overfilled. Leave headspace to allow for expansion and store the filled waste containers in a secure area.

6.3 Waste Disposal

1. Hazardous waste is accumulated in the Hazardous Waste Storage area for each FSU facility. Instructions are provided on the door of the storage room for inventorying and labeling of waste containers.
2. A licensed waste hauler is contracted to make hazardous waste pickups on a regular basis, according to state and federal regulations.
3. Manifest tracking
 - a) Designated person from FSU (CHO) signs off on pick-up,
 - b) SHERM retains the ‘generator’ copy, Transporter keeps all others.

- c) “Facility Signed Copy” is mailed back to FSU after delivery is complete and is kept for 3 years. State of Michigan must also be provided with a copy from either FSU or the disposal facility, depending upon arrangements made with the disposal facility.
 - d) Copies of universal waste manifests are kept in the universal waste file and log is updated. Exception: For universal waste (i.e. needles, elemental mercury, etc.) there will be no white copy received or sent back to Michigan DEQ.
- 4. All hazardous chemical waste should be segregated and labeled according to FSU waste disposal guidelines. Special attention should be given to the following areas:
 - a) Glass containing no hazardous material must be kept in receptacles labeled “Broken Glass”.
 - b) Chemical waste is to be collected in containers labeled "Hazardous Waste", the category of hazard, the specific chemical or reagent if known and the date.
 - c) Items such as mercury thermometers, used fluorescent light bulbs, and waste rechargeable batteries must be labeled with the words “Universal Waste”.
 - d) Use separate containers for metal, glass and plastic sharps. Collect sharps contaminated with biohazardous materials in rigid, leakproof, puncture resistant containers which have been labeled with the universal biohazard symbol (see example above).

7.0 EMERGENCY RESPONSE AND MEDICAL PROCEDURES

7.1 BASIC STEPS FOR EMERGENCIES AND SPILL RESPONSE

The following situations identify non-medical emergencies that may occur in laboratory areas:

1. The situation is unclear to the person causing or discovering a spill or reaction.
2. The release requires evacuation.
3. The release involves or poses a threat of:
 - fire, suspected fire, explosion or other imminent danger,
 - conditions that are Immediately Dangerous to Life and Health (IDLH),
 - high levels of exposure to toxic substances.
4. The person(s) in the work area is uncertain of their qualification to handle the situation with the personal protective equipment (PPE) and response equipment that has been provided, especially if the exposure limit could easily be exceeded.

Only trained employees may respond to an emergency. If you have not received training, specific for the emergency and subsequent response, call the emergency contact number(s) on Page 2 of this Plan. After the situation has been made safe, an incident report (see appendix) should be completed describing the cause, response actions, current condition, and identifying any persons who may have been exposed.

Conversely, if the conditions do not meet the criteria described above, the situation may not be an emergency and can be responded to locally. The following situations ARE NOT emergencies:

1. The person causing or discovering the release understands the properties and can make an informed decision as to the exposure level.
2. The release can be appropriately cleaned up by the lab personnel using spill kits.
3. The materials are limited in quantity, exposure potential, or toxicity and present minor safety or health hazards to persons in the immediate work area or those assigned to clean up the activity.

7.2 FIRE

There are two categories of fires that may occur in the lab: minor or incipient fires and those that are larger and may involve the structure of the facility. In both of these situations it is most appropriate to call 9-1-1. FSU faculty and staff, who have received proper training (offered by SHERM), may (voluntarily) respond to incipient fires by using the nearest fire extinguisher. For larger fires, the proper response is;

- e) Pull the fire alarm, if available, or dial 9-1-1.
- f) Evacuate to a safe location.
- g) Communicate with Public Safety or other responders as to the nature of the incident.

7.3 SPILL RESPONSE

7.3.1 Minor Spills

Minor spills are small quantities of material that you understand the hazards of and are comfortable that you have the training and ability and to clean up appropriately. If you are unsure of the hazard of a spill or proper response procedures contact your Lab Supervisor, CHO or Public Safety. All minor spills should be cleaned up immediately.

Minor spill cleanup procedures:

1. Notify everyone in the immediate area that you have a spill
2. Assess the hazard and your ability to clean up properly.
3. Locate the spill kit and identify appropriate protective equipment. At a minimum always use gloves and protective eyewear.
4. Use an appropriate absorbent to confine or contain the spill. Strong acids or bases may need to use a neutralizing absorbent. Do not use paper towels.
5. Properly dispose of the absorbent and clean the spilled area.
 - a) For non-reactive spills: scoop into a plastic disposal bag and sweep solid materials into a dustpan and place in a sealed container. Dispose of waste as normal trash as long as substance is non-volatile and non-hazardous waste.
 - b) For reactive or potentially reactive spills: scoop into an appropriate container. Wet mop the dry substances to avoid spreading hazardous dust, provided it is non-water reactive. If spilled chemical is a volatile solvent, transfer disposal bag to a hood. Follow the FSU policy for disposal.

7.3.2 Potentially Hazardous Spills

These may be larger in quantity or spills of highly hazardous materials including materials of low LD50, carcinogens or reproductive toxins, reactive, corrosive or flammable liquids, or metals, and materials of unknown toxicity.

Potentially hazardous spill response procedures

1. Notify everyone in the immediate area of the potentially hazardous spill.
2. Vacate the area, close the door behind you, and move to a safe location.
3. If the situation may cause airborne contaminants or risk of fire or explosion, pull fire alarm to evacuate the building.
4. Call 9-1-1 and provide details of the situation.
5. Have someone knowledgeable of the situation meet Public Safety/EMS upon their arrival at the building.

Evacuation of the building is mandatory if chemicals or contaminants can enter the air circulation system of the building.

7.3.3 Mercury [MJM13] Spills

These may occur when mercury-containing devices are broken. To avoid such spills from occurring all mercury containing devices should be replaced. In case of a spill or broken mercury containing device, contact your Lab Supervisor or CHO.

Mercury reductions plans must be followed for mercury containing devices or mercury containing chemicals. SCI, VFS and PHR are all under specific mercury reductions plans. The city of Big Rapids prohibits the discharge of mercury into the sewer. All mercury containing devices and chemicals are required to be registered with the AALSD as described in plans.

Mercury spill response procedures

1. use a trapped vacuum line attached to a tapered glass tube or rubber bulb aspirator to pick up mercury droplets. Do not use a domestic or commercial vacuum cleaner.
2. Cover small droplets in accessible areas with one of the following:
 - a. sodium polysulfide solution
 - b. powdered sulfur
 - c. silver metal compounds

- d. dry ice to freeze the mercury droplets
3. Place residue in container for hazardous waste collection.

For all potentially hazardous spills a report describing the spill should be sent to the area lab supervisor, and CHO.

7.4 POWER OUTAGES

The main risk during a power outage is loss of lab ventilation and climate control. Emergency lighting is provided for emergency egress. If emergency lighting and fire alarms ARE NOT operable, evacuate the building. If adequate lighting is provided, leave the area after the following steps have been taken. It is the responsibility of the lab supervisor/PI to ensure that each of the following occurs:

1. Place lids on all open containers of volatile chemicals
2. Lower the sash on chemical fume hoods
3. Shut down all equipment (leave cooling water and purge gases on as necessary)
4. Turn off ignition sources
5. Secure or isolate reactions that are underway (boiling liquid on a hot plate, distillations)
6. Close fire doors
7. Take your books, coats, purse/wallet, keys, etc.
8. Lock outside door to lab.

7.5 INJURY AND ILLNESS

For medical emergencies dial 911. For employees seeking non-emergency medical treatment, under current FSU policies and procedures, affected employees must seek care from an approved facility (list maintained by SHERM). Injured students seeking non-emergency medical attention are to make their own decisions regarding their medical care (see policy:

<https://www.ferris.edu/HTMLS/administration/buspolletter/treat.917.htm>). The supervisor or instructor must ensure the appropriate injury report forms are completed. If you have any questions regarding injury and illness procedures, contact your supervisor or instructor.

Minor First Aid: In most situations emergency medical care is available within minutes of FSU labs.

1. Do not dispense or administer any medications, including aspirin.
2. Do not put any ointments or creams on wounds or burns. Use cool water.
3. Review the SDS for specific first aid information for a given chemical.

Eye Splash:

1. Remove victim from spill area only if an attempt to rescue does not present a danger to the rescuers.
2. Lead the victim(s) immediately to an emergency eyewash facility.
3. Assist the victim as needed. The goal is to flush the eyes and upper portion of the face.
4. Flush for at least 15 minutes or longer if pain persists.
5. Contact the CHO and/or emergency response personnel and inform them of the incident and possible chemical(s) involved.

Chemical Body Splash:

1. Remove victim(s) from the spill area to fresh air only if an attempt to rescue victim(s) does not present a danger to the rescuers.
2. Don appropriate personal protective equipment (gloves, eye protection, etc.)
3. Remove contaminated clothing while under an emergency shower.
4. Flood affected area of the body with cold water for at least 15 minutes or longer if pain persists.
5. Wash skin with mild soap and water – do not use neutralizing chemicals, creams, lotions or salves.

6. Contact the CHO and/or emergency response personnel and inform them of the incident and possible chemical(s) involved.

Whenever emergency shower or eye wash stations are used inform Public Safety.

7.6 MEDICAL CONSULTATIONS AND EXAMINATIONS

In certain situations, FSU will provide faculty, staff, and student employees, who work with hazardous materials an opportunity to receive medical attention, including any follow-up examinations which the examining physician determines to be necessary, under the following circumstances:

1. An employee must be provided an opportunity to receive an appropriate examination when he or she develops signs or symptoms associated with hazardous materials to which there may have been exposure in the laboratory.
2. If exposure monitoring reveals an exposure level routinely above the action level (or in the absence of an action level, the Permissible Exposure Limit) for an OSHA regulated substance for which there are exposure monitoring and medical surveillance requirements, medical surveillance shall be established for the affected employee as prescribed by the particular standard.
3. Whenever an event takes place in the work area, such as a spill, leak, explosion, or other occurrence resulting in the likelihood of a hazardous exposure, the affected employee shall be provided an opportunity for a medical consultation. Such consultations shall be for determining the need for a medical examination.

All medical consultations and examinations must be performed by or under the direct supervision of a licensed physician and must be provided without cost to the employee, without loss of pay and at a reasonable time and place.

The following information shall be provided to the examining physician:

1. The identity of the hazardous chemical(s) to which the employee may have been exposed.
2. A description of the conditions surrounding the exposure, including available quantitative exposure data.
3. A description of the signs and symptoms of exposure that the employee is experiencing, if any.

SHERM shall obtain a written opinion from the examining physician that includes:

1. The results of the medical examination and any associated tests and any recommendation for further medical follow-up.
2. Any medical condition which may be revealed in the course of the examination which may place the employee at increased risk as a result of exposure to a hazardous chemical found in the workplace.
3. A statement that the employee has been informed by the physician of the results of the consultation or medical examination and any medical condition that may require further examination or treatment.
4. The written opinion of the physician shall not reveal specific finding of diagnoses unrelated to occupational exposure.



Accident records for employees should be written and submitted to SHERM. Forms are available at www.ferris.edu/SHERM .

8.0 APPENDICES

Appendix A	FSU Accident/Injury Report Form
Appendix B	Incompatibility of Common Laboratory Chemicals
Appendix C	Flammable & Combustible Liquid Containment & Storage Requirements
Appendix D	Common Laboratory Corrosives
Appendix E	Common Laboratory Oxidizers
Appendix F	Common Peroxide Formers & Detection and Inhibition of Peroxides
Appendix G	Shock Sensitive and Explosive Chemicals
Appendix H	FSU Chemical Safety Laboratory Checklist
Appendix I	Policy for Termination of Laboratory
Appendix J	Industrial Toxicology-Overview
Appendix K	FSU Respiratory Protection Policy
Appendix L	Volunteers in Labs Template
Appendix M	Definitions

APPENDIX A: FSU INCIDENT AND INJURY REPORT FORM

Employee injury report located at: <https://www.ferris.edu/HTMLS/administration/adminandfinance/finance/sherm/pdfs-docs/IncidentReportForm.pdf>; Non-employee/student injury report located at: <https://www.ferris.edu/HTMLS/administration/adminandfinance/finance/sherm/pdfs-docs/student-injury.pdf>

 Ferris State University EMPLOYEE INJURY / ILLNESS / INCIDENT INVESTIGATION & REPORT Report All Work Related Injuries to (231)591-3848 Immediately					
Office Use Only:		Rec: <input type="checkbox"/> Yes <input type="checkbox"/> No		Rpt. NO.	
Associate Info	(1) Name of Employee		(2) ID Number	(3) Date of Birth	(4) Employee Type <input type="checkbox"/> AFSCME <input type="checkbox"/> Clerical <input type="checkbox"/> Faculty <input type="checkbox"/> Staff <input type="checkbox"/> Student <input type="checkbox"/> Other
	(5) Home Address		(6) Home Phone Number	(7) Hire Date	
	(8) Tax Filing Status <input type="checkbox"/> Male <input type="checkbox"/> Single <input type="checkbox"/> Head of Household <input type="checkbox"/> Female <input type="checkbox"/> Married Filing Separate <input type="checkbox"/> Married Filing Joint		(9) Dependents Total Number Under Age 16		(10) Work Schedule <input type="checkbox"/> Mon <input type="checkbox"/> Thu <input type="checkbox"/> Tue <input type="checkbox"/> Fri <input type="checkbox"/> Wed <input type="checkbox"/> Sat <input type="checkbox"/> Sun
Location Info	(11) Date of Incident	(12) Campus Location <input type="checkbox"/> FSU Big Rapids <input type="checkbox"/> FSU - GR <input type="checkbox"/> Kendall <input type="checkbox"/> Other	(13) Department	(14) General Task / Job Classification	
	(15) Time of Incident am <input type="checkbox"/> pm <input type="checkbox"/>		(16) General Location / Building	(17) Specific Location of Incident	
	(18) Start Time of Shift am <input type="checkbox"/> pm <input type="checkbox"/>		(19) Specific Activity at Time of Injury or Just Before Injury Occurred		
Incident Info	(20) Body Part(s) affected		(21) Object(s) Causing Injury / Illness		 (22) Click in the general effected area(s). Select the specific area(s) effected from the drop-down menu. Other: _____ <input type="checkbox"/> Front <input type="checkbox"/> Back <input type="checkbox"/> Left <input type="checkbox"/> Right
	(23) Cause of Injury / Illness or How Injury Occurred				
	(24) Type of Injury / Illness <input type="checkbox"/> Abrasion <input type="checkbox"/> Contusion/Bruise <input type="checkbox"/> Rash <input type="checkbox"/> Amputation <input type="checkbox"/> Cut / Puncture <input type="checkbox"/> Repetitive <input type="checkbox"/> Bite / Sting <input type="checkbox"/> Dislocation <input type="checkbox"/> Respiratory <input type="checkbox"/> Burn <input type="checkbox"/> Fracture <input type="checkbox"/> Sprain/Strain <input type="checkbox"/> Other				
Misc. Info	(25) Property damage <input type="checkbox"/> Yes <input type="checkbox"/> No	(26) Vehicle involved <input type="checkbox"/> Yes <input type="checkbox"/> No	(27) Proper procedure used <input type="checkbox"/> Yes <input type="checkbox"/> No	(28) Proper PPE used for job <input type="checkbox"/> Yes <input type="checkbox"/> No	(29) Working with <input type="checkbox"/> Crew <input type="checkbox"/> Alone
	(30) Near Miss <input type="checkbox"/> Yes <input type="checkbox"/> No				
Employee & Supervisor Description	(31) Witness list and Statement				
	(32) Employee Statement of Facts				
Actions Taken	(33) Supervisor's Investigation Findings				
Medical	(34) Actions taken to prevent recurrence				
	(35) Treatment Location <input type="checkbox"/> Birkam Health Center <input type="checkbox"/> None <input type="checkbox"/> Off Site Medical Center (complete 36 - 38)		(36) Physician or other Health Care Professional and Phone Number		
	Employee must: A) Return copies of all paperwork from Medical Center to SHERM B) Notify SHERM of all Medical Treatment		(37) Facility Name and (38) Address		
Signatures	(39) Supervisor (print)		(40) Supervisor (sign)	(41) Date	
	ext. _____				
	(42) Employee (print)		(43) Employee (sign)	(44) Date	

Rev. 7/3/2018 Forward completed original to: FSU - Workers Comp., 420 Oak St. PRK 153, Big Rapids, MI 49307 (231)591-2978 fax: (231)591-3848 or (800)592-6499 ext. 2150
cc: ☐ Department Head ☐ Employee ☐ Supervisor

APPENDIX B: INCOMPATIBILITY OF COMMON LABORATORY CHEMICALS

When certain hazardous chemicals are stored or mixed together, violent reactions may occur because the chemicals are unsuitable for mixing, or are incompatible. Classes of incompatible chemicals should be segregated from each other during storage, according to hazard class. Use the following general guidelines for hazard class storage:

1. Flammable/Combustible Liquids and Organic Acids
2. Flammable Solids
3. Mineral Acids
4. Caustics
5. Oxidizers
6. Perchloric Acid
7. Compressed Gases

Before mixing any chemicals, refer to this partial list, the chemicals' SDS's, or contact the Chemical Hygiene Officer to verify compatibility:

CHEMICAL	INCOMPATIBLE CHEMICAL(S)
Acetic acid	aldehyde, bases, carbonates, hydroxides, metals, oxidizers, peroxides, phosphates, xylene
Acetylene	halogens (chlorine, fluorine, etc.), mercury, potassium, oxidizers, silver
Acetone	acids, amines, oxidizers, plastics
Alkali and alkaline earth metals	acids, chromium, ethylene, halogens, hydrogen, mercury, nitrogen, oxidizers, plastics, sodium chloride, sulfur
Ammonia	acids, aldehydes, amides, halogens, heavy metals, oxidizers, plastics, sulfur
Ammonium nitrate	acids, alkalis, chloride salts, combustible materials, metals, organic materials, phosphorous, reducing agents, urea
Aniline	acids, aluminum, dibenzoyl peroxide, oxidizers, plastics
Azides	acids, heavy metals, oxidizers
Bromine	acetaldehyde, alcohols, alkalis, amines, combustible materials, ethylene, fluorine, hydrogen, ketones (acetone, carbonyls, etc.), metals, sulfur
Calcium oxide	acids, ethanol, fluorine, organic materials
Carbon (activated)	alkali metals, calcium hypochlorite, halogens, oxidizers
Carbon tetrachloride	benzoyl peroxide, ethylene, fluorine, metals, oxygen, plastics, silanes
Chlorates	powdered metals, sulfur, finely divided organic or combustible materials
Chromic acid	acetone, alcohols, alkalis, ammonia, bases
Chromium trioxide	benzene, combustible materials, hydrocarbons, metals, organic materials, phosphorous, plastics
Chlorine	alcohol's, ammonia, benzene, combustible materials, flammable compounds (hydrazine), hydrocarbons (acetylene, ethylene, etc.), hydrogen peroxide, iodine, metals, nitrogen, oxygen, sodium hydroxide
Chlorine dioxide	hydrogen, mercury, organic materials, phosphorous, potassium hydroxide, sulfur
Copper	calcium, hydrocarbons, oxidizers
Hydroperoxide	reducing agents
Cyanides	acids, alkaloids, aluminum, iodine, oxidizers, strong bases
Flammable liquids	ammonium nitrate, chromic acid, hydrogen peroxide, nitric acid, sodium peroxide, halogens
Fluorine	alcohol's, aldehydes, ammonia, combustible materials, halocarbons, halogens, hydrocarbons, ketones, metals, organic acids
Hydrocarbons (Such as butane, propane benzene, turpentine, etc.)	acids, bases, oxidizers, plastics

Hydrofluoric acid	metals, organic materials, plastics, silica (glass), (anhydrous) sodium
Hydrogen peroxide	acetaldehyde, acetic acid, acetone, alcohol's carboxylic acid, combustible materials, metals, nitric acid, organic compounds, phosphorous, sulfuric acid, sodium, aniline
Hydrogen sulfide	acetaldehyde, metals, oxidizers, sodium
Hypochlorites	acids, activated carbon
Iodine	acetaldehyde, acetylene, ammonia, metals, sodium
Mercury	acetylene, aluminum, amines, ammonia, calcium, fulminic acid, lithium, oxidizers, sodium
Nitrates	acids, nitrites, metals, sulfur, sulfuric acid
Nitric acid	acetic acid, acetonitrile, alcohol's, amines, (concentrated) ammonia, aniline, bases, benzene, cumene, formic acid, ketones, metals, organic materials, plastics, sodium, toluene
Oxalic acid	oxidizers, silver, sodium chlorite
Oxygen	acetaldehyde, secondary alcohol's, alkalis and alkalines, ammonia, carbon monoxide, combustible materials, ethers, flammable materials, hydrocarbons, metals, phosphorous, polymers
Perchloric acid	acetic acid, alcohols, aniline, combustible materials, dehydrating agents, ethyl benzene, hydriotic acid, hydrochloric acid, iodides, ketones, organic material, oxidizers, pyridine
Peroxides, organic	acids (organic or mineral)
Phosphorus (white)	oxygen (pure and in air), alkalis
Potassium	acetylene, acids, alcohols, halogens, hydrazine, mercury, oxidizers, selenium, sulfur
Potassium chlorate	acids, ammonia, combustible materials, fluorine, hydrocarbons, metals, organic materials, sugars
Potassium perchlorate (also see chlorates)	alcohols, combustible materials, fluorine, hydrazine, metals, organic matter, reducing agents, sulfuric acid
Potassium permanganate	benzaldehyde, ethylene glycol, glycerol, sulfuric acid
Silver	acetylene, ammonia, oxidizers, ozonides, peroxyformic acid
Sodium	acids, hydrazine, metals, oxidizers, water
Sodium nitrate	acetic anhydride, acids, metals, organic matter, peroxyformic acid, reducing agents
Sodium peroxide	acetic acid, benzene, hydrogen sulfide metals, oxidizers, peroxyformic acid, phosphorous, reducers, sugars, water
Sulfides	Acids
Sulfuric acid	potassium chlorates, potassium perchlorate, potassium permanganate

References:

Safety Data Sheets, various chemical companies.

APPENDIX C: FLAMMABLE AND COMBUSTIBLE STORAGE AND CONTAINMENT

Flammable and combustible chemicals are the most commonly used hazardous chemicals. The hazard of a flammable or combustible chemical is based on its flash point, and, in the case of a flammable chemical, its boiling point as well. The National Fire Protection Association (NFPA) has identified flammability classes from the flash point and boiling point data of chemicals. The following table lists some common flammable and combustible chemicals, their flash points and boiling points, and associated NFPA flammability classes:

Chemical	Flash Point		Boiling Point		NFPA Class
	° F	° C	° F	° C	
Acetaldehyde	-38	-39	69	21	IA
Dimethyl sulfide	-36	-38	99	37	IA
Ethyl ether	-49	-45	95	35	IA
Ethylene oxide	-20	-29	55	13	IA
Pentane	-57	-49	97	36	IA
Propane	-157	-105	-44	-42	IA
Benzene	12	-11	176	80	IB
Carbon disulfide	-22	-30	115	46	IB
Cyclohexane	-4	-20	179	81	IB
Ethyl alcohol	55	13	173	78	IB
n-Hexane	-7	-22	156	69	IB
Isopropyl alcohol	53	12	180	82	IB
Methyl alcohol	52	11	149	65	IB
Methyl ethyl ketone	16	-9	176	80	IB
Pyridine	68	20	239-	116	IB
Tetrahydrofuran	6	-14	153	67	IB
Toluene	40	4	231	111	IB
Triethylamine	20	-7	193	89	IB
tert Butyl isocyanate	80	27	185-	85-86	IC

Chemical	Flash Point		Boiling Point		NFPA Class
	° F	° C	° F	° C	
Chlorobenzene	82	28	270	132	IC
Epichlorohydrin	88	31	239-	115-	IC
2-Nitropropane	75	24	248	120	IC
Xylene	81-90	27-	280-	138-	IC
Acetic Acid, glacial	103	39	244	48	II
Bromobenzene	118	48	307-	153-	II
Formic Acid	156	69	213	101	II
Morpholine	100	38	263	128	II
Stoddard Solvent	100-	38-	300-	150-	II
Benzaldehyde	145	63	352	178	IIIA
Cyclohexanol	154	68	322	161	IIIA
Methacrylic Acid	170	77	316	158	IIIA
Nitrobenzene	190	88	412	211	IIIA
Tetrahydronaphthalene	160	71	406	208	IIIA
Benzyl Alcohol	213	101	401	205	IIIB
Caproic Acid	215	102	400	204	IIIB
Ethylene Glycol	232	111	388	198	IIIB
Phenyl Ether	239	115	498	258	IIIB
Stearic Acid	385	196	726	386	IIIB

References: Safety Data Sheets and the National Fire Protection Agency document "NFPA 321: Classification of Flammable and Combustible Liquids, 1991 Edition."

Flammable and Combustible Liquid Containment and Storage Requirements

Containment:

Only approved containers and metal portable tanks authorized by NFPA 30 shall be used to store flammable liquids.

Container	Flammable Class			Combustible Class	
	IA	IB	IC	II	III
Glass	1 pt*	1 qt*	1 gal	1 gal	5 gal
Metal or Approved Plastic	1 gal	5 gal	5 gal	5 gal	5 gal
Safety Cans	2 gal	5 gal	5 gal	5 gal	5 gal
Metal Drums	60 gal	60 gal	60 gal	60 gal	60 gal
Approved Metal Portable Tanks	660 gal	660 gal	660 gal	660 gal	660 gal
Polyethylene	1 gal	5 gal	5 gal	60 gal	60 gal

*Class IA and IB liquids may be stored up to one gallon in glass containers if liquid purity would be affected by storage in metal containers or if metal containers could undergo excessive corrosion by the contained liquid.

Storage

Only NFPA 45 approved amounts of flammable liquids shall be stored in laboratory units outside of flammable liquid storage rooms.

Flammable / Combustible Class	Maximum Quantity per 100ft ² of Laboratory Unit	Maximum Quantity per Laboratory Unit	
		Unsprinklered	Sprinklered
List as Class A Lab			
I	20 gallons	600 gallons	1200 gallons
I, II and IIIA	40 gallons	800 gallons	1600 gallons
List as Class B Lab			
I	10 gallons	300 gallons	600 gallons
I, II and IIIA	20 gallons	400 gallons	800 gallons
List as Class C Lab			
I	4 gallons	150 gallons	300 gallons
I, II and IIIA	8 gallons	200 gallons	400 gallons

- The amounts above include quantities stored in approved storage cabinets and safety cans. Allowable quantities stored outside of approved storage cabinets and safety cans are 50% of the quantities listed above.
- Laboratories listed as Class A shall be considered high hazard laboratories and **shall not be used as instructional laboratories.**
- Laboratories listed as Class B shall be considered intermediate hazard laboratories.
- Laboratories listed as Class C shall be considered low hazard laboratories.
- **Should Class B or C laboratories be used for instructional purposes, quantities of flammable and combustible liquids shall be 50% of those listed in the above table.**

APPENDIX D: COMMON LABORATORY CORROSIVES

ORGANIC ACIDS	ORGANIC BASES	INORGANIC ACIDS
Formic Acid	Ethylenediamine	Hydrofluoric Acid
Acetic Acid (Glacial)	Ethylimine	Hydrochloric Acid
Propionic Acid	Tetramethylethylenediamine	Hydrobromic Acid
Butyric Acid	Hexamethylenediamine	Hydriotic Acid
Chloroacetic Acid	Trimethylamine aq. soln.	Sulfuric Acid
Trichloroacetic Acid	Triethylamine	Chromerge™
Acetyl Chloride	Phenylhydrazine	No-Chromix™
Acetyl Bromide	Piperazine	Chlorosulfonic Acid
Chloroacetyl Chloride	Hydroxylamine	Sulfuryl Chloride
Oxalic Acid	Tetramethylammonium Hydroxide	Bromine Pentafluoride
Propionyl Chloride		Thionyl Chloride
Propionyl Bromide	ELEMENTS	Tin Chloride
Acetic Anhydride	Fluorine (gas)	Tin Bromide
Methyl Chloroformate	Chlorine (gas)	Titanium Tetrachloride
Dimethyl Sulfate	Bromine (liquid)	Perchloric Acid
Chlorotrimethylsilane	Iodine (crystal)	Nitric Acid
Dichlorodimethylsilane	Phosphorus	Phosphoric Acid
Phenol		Phosphorus Trichloride
Benzoyl Chloride		Phosphorus Tribromide
Benzoyl Bromide	INORGANIC BASES	Phosphorus Pentachloride
Benzyl Chloride	Ammonium Hydroxide	Phosphorus Pentoxide
Benzyl Bromide	Calcium Hydroxide	
Salicylic Acid	Sodium Hydroxide	
	Potassium Hydroxide	ACID SALTS
	Calcium Hydride	Aluminum Trichloride
	Sodium Hydride	Antimony Trichloride
	Hydrazine	Ammonium Bifluoride
	Ammonium Sulfide	Calcium Fluoride
	Calcium Oxide	Ferric Chloride
		Sodium Bisulfate
		Sodium Fluoride

References:

The Foundations of Laboratory Safety, S. R. Rayburn, 1990.
Prudent Practices for Handling Hazardous Chemicals in Laboratories, National Research Council, 1981.
Improving Safety in the Chemical Laboratory, 2nd Ed., J. A. Young, 1991.
 Safety Data Sheets, various chemical companies.

APPENDIX E: COMMON LABORATORY OXIDIZERS

Oxidizers react with other chemicals by giving off electrons and undergoing reduction. Uncontrolled reactions of oxidizers may result in a fire or an explosion, causing severe property damage or personal injury. Use oxidizers with extreme care and caution and follow all safe handling guidelines specified in the SDS.

Bleach	Nitrites
Bromates	Nitrous oxide
Bromine	Ozanates
Butadiene	Oxides
Chlorates	Oxygen
Chloric Acid	Oxygen difluoride
Chlorine	Ozone
Chlorite	Peracetic Acid
Chromates	Perhaloate
Chromic Acid	Perborates
Dichromates	Percarbonates
Fluorine	Perchlorates
Haloate	Perchloric Acid
Halogens	Permanganates
Hydrogen Peroxide	Peroxides
Hypochlorites	Persulfate
Iodates	Sodium Borate Perhydrate
Mineral Acid	Sulfuric Acid
Nitrates	
Nitric Acid	

APPENDIX F: PEROXIDIZABLE CHEMICALS

Part A. Chemicals that form explosive levels of peroxides without concentration

Butadiene ^a	Divinylacetylene	Tetrafluoroethylene ^a	Vinylidene chloride	Chloroprene ^a	Isopropyl ether
------------------------	------------------	----------------------------------	---------------------	--------------------------	-----------------

Part B. Chemicals that form explosive levels of peroxides on concentration

Acetal	Diacetylene	2-Hexanol	2-Phenylethanol
Acetaldehyde	Dicyclopentadiene	Methylacetylene	2-Propanol
Benzyl alcohol	Diethyl ether	3-Methyl-1-butanol	Tetrahydrofuran
2-Butanol	Diethylene glycol dimethyl ether	Methylcyclopentane	Tetrahydronaphthalene
Cumene	(diglyme)	Methyl isobutyl ketone	Vinyl ethers
Cyclohexanol	Dioxanes	4-Methyl-2-pentanol	Other secondary alcohols
2-Cyclohexen-1-ol	Ethylene glycol dimethyl ether	2-Penten-1-ol	
Cyclohexene	(glyme)	4-Penten-1-ol	
Decahydronaphthalene	4-Heptanol	1-Phenylethanol	

Part C. Chemicals that may autopolymerize because of peroxide accumulation

Acrylic acid ^b	Chlorotrifluoroethylene	Vinyl acetate	Chloroprene ^c	Vinylidene chloride
Acrylonitrile ^b	Methyl methacrylate ^b	Vinylacetylene	Tetrafluoroethylene ^c	
Butadiene ^c	Styrene	Vinyl chloride	Vinylpyridine	

Part D. Chemicals that may form peroxides but cannot clearly be placed in sections A-C

Acrolein	tert-Butyl methyl ether	Di(1-propynyl) ether ^f	4-Methyl-2-pentanone
Allyl ether ^d	n-Butyl phenyl ether	Di(2-propynyl) ether	n-Methylphenetole
Allyl ethyl ether	n-Butyl vinyl ether	Di-n-propoxymethane ^d	2-Methyltetrahydrofuran
Allyl phenyl ether	Chloroacetaldehyde diethylacetal ^d	1,2-Epoxy-3-isopropoxypropane ^d	3-Methoxy-1-butyl acetate
p-(n-Amyloxy)benzoyl chloride	2-Chlorobutadiene	1,2-Epoxy-3-phenoxypropane	2-Methoxyethanol
n-Amyl ether	1-(2-Chloroethoxy)-2-phen- oxyethane	Ethoxyacetophenone	3-Methoxyethyl acetate
Benzyl n-butyl ether ^d		1-(2-Ethoxyethoxy)ethyl acetate	2-Methoxyethyl vinyl ether
Benzyl ether ^d	Chloroethylene	2-Ethoxyethyl acetate	Methoxy-1,3,5,7-cycloocta Tetraene
Benzyl ethyl ether ^d	Chloromethyl methyl ether ^e	(2-Ethoxyethyl)-o-benzoyl Benzoate	
Benzyl methyl ether	§-Chlorophenetole		§-Methoxypropionitrile
Benzyl 1-naphthyl ether ^d	o-Chlorophenetole	1-Ethoxynaphthalene	m-Nitrophenetole
1,2-Bis(2-chloroethoxy)ethane	p-Chlorophenetole	o,p-Ethoxyphenyl isocyanate	1-Octene
Bis(2-ethoxyethyl) ether	Cyclooctene ^d	1-Ethoxy-2-propyne	Oxybis(2-ethyl acetate)
Bis(2-(methoxyethoxy)ethyl) ether	Cyclopropyl methyl ether	3-Ethoxypropionitrile	Oxybis(2-ethyl benzoate)
	Diallyl ether ^d	2-Ethylacrylaldehyde oxime	§,§-Oxydipropionitrile
Bis(2-chloroethyl) ether	p-Di-n-butoxybenzene	2-Ethylbutanol	1-Pentene
Bis(2-ethoxyethyl) adipate	1,2-Dibenzoyloxyethane ^d	Ethyl §-ethoxypropionate	Phenoxyacetyl chloride

Bis(2-ethoxyethyl) phthalate	p-Dibenzoyloxybenzene ^d	2-Ethylhexanal	Æ-Phenoxypropionyl chloride
Bis(2-methoxyethyl) carbonate	1,2-Dichloroethyl ethyl ether	Ethyl vinyl ether	Phenyl o-propyl ether
Bis(2-methoxyethyl) ether	2,4-Dichlorophenetole	Furan p-Phenylphenetone	
Bis(2-methoxyethyl)phthalate	Diethoxymethane ^d	2,5-Hexadiyn-1-ol	n-Propylether
Bis(2-methoxymethyl) adipate	2,2-Diethoxypropane	4,5-Hexadien-2-yn-1-ol	n-Propyl isopropyl ether
Bis(2-n-butoxyethyl) phthalate	Diethyl ethoxymethylenemalonate	n-Hexyl ether	Sodium 8,11,14-eicosa Tetraenoate
Bis(2-phenoxyethyl) ether	Diethyl fumarated	o,p-Iodophenetole	
Bis(4-chlorobutyl) ether	Diethyl acetal ^d Isoamyl benzyl ether ^d	Sodium ethoxyacetylde ^f	
Bis(chloromethyl) ether ^c	Diethylketene ^f	Isoamyl ether ^d	Tetrahydropyran
2-Bromomethyl ethyl ether	m,o,p-Diethoxybenzene	Isobutyl vinyl ether	Triethylene glycol diacetate
§-Bromophenetole	1,2-Diethoxyethane	Isophorone ^d	Triethylene glycol dipropionate
o-Bromophenetole	Dimethoxymethane ^d	p-Isopropoxypropionitrile ^d	1,3,3-Trimethoxypropene ^d
p-Bromophenetole	1,1-Dimethoxyethane ^d	Isopropyl 2,4,5-trichlorophenoxy- Acetate	1,1,2,3-Tetrachloro-1,3- Butadiene
3-Bromopropyl phenyl ether	Dimethylketene ^f		
1,3-Butadiyne	3,3-Dimethoxypropene	Limonene	4-Vinyl cyclohexene
Buten-3-yne	2,4-Dinitrophenetole	1,5-p-Methadiene	Vinylenecarbonate
tert-Butyl ethyl ether	1,3-Dioxepane ^d	Methyl p-(n-amylxy)benzoate	Vinylidene chlorid ^d

- When stored as a liquid monomer
- Although these chemicals form peroxides, no explosions involving these monomers
- When stored in liquid form, these chemicals form explosive levels of peroxides without concentration. They may also be stored as a gas in gas cylinders. When stored as a gas, these chemicals may autopolymerize because of peroxide accumulation.
- These chemicals easily form peroxides and should probably be considered under part B.
- OSHA-regulated carcinogen
- Extremely reactive and unstable compound.

Safe Storage Period for Peroxide Forming Chemicals

Description	Period
Unopened chemicals from manufacturer	18 months
Opened containers	
Chemicals in Part A	3 months
Chemicals in Parts B and D	12 months
Uninhibited chemicals in Part C	24 hours
Inhibited chemicals in Part C	12 months ^a

****Do not store under inert atmosphere, oxygen required for inhibitor to function.****

DETECTION AND INHIBITION OF PEROXIDES BASIC PROTOCOLS

Ferrous Thiocyanate Detection Method

Ferrous thiocyanate will detect hydroperoxides with the following test:

- Mix a solution of 5 ml of 1 % ferrous ammonium sulfate, 0.5 ml of 1 N sulfuric acid and 0.5 ml of 0.1 N ammonium thiocyanate (if necessary decolorize with a trace of zinc dust)
- Shake with an equal quantity of the solvent to be tested

3. If peroxides are present, a red color will develop

Potassium Iodide Detection Method

1. Add 1 ml of a freshly prepared 10% solution of potassium iodide to 10 ml of ethyl ether in a 25 ml glass-stoppered cylinder of colorless glass protected from light (both components are clear)
2. A resulting yellow color indicates the presence of 0.005% peroxides

Inhibition of Peroxides

1. Storage and handling under an inert atmosphere is a useful precaution
2. Addition of 0.001 % hydroquinone, diphenylamine, polyhydroxyphenols, aminophenols, or arylamines may stabilize ethers and inhibit formation of peroxides.
3. Dowex-1^R has been reported effective for inhibiting peroxide formation in ethyl ether.
4. 100 ppm of 1-naphthol effective for peroxide inhibition in isopropyl ether.
5. Hydroquinone effective for peroxide inhibition in tetrahydrofuran.
6. Stannous chloride or ferrous sulfate effective for peroxide inhibition in dioxane.

Peroxides Test Strips

These test strips are available from EM Scientific, cat. No. 10011-1 or from Lab Safety Supply, cat. No. 1162. These strips quantify peroxides up to a concentration of 25 ppm. Aldrich Chemical has a peroxide test strip, cat. No. Z10, 168-0, that measure up to 100 ppm peroxide. The actual concentration at which peroxides become hazardous is not specifically stated in the literature. A number of publications use 100 ppm as a control valve for managing the material safely.

Please note that these methods are BASIC protocols. Should a researcher perform one of these methods, all safety precautions should be thoroughly researched.

Sources:

1. Furr, Keith Handbook of Lab Safety, 4th ed., CRC Press, 1995
2. Kelly, Richard J., Review of Safety Guidelines for Peroxidizable Organic Chemicals, Chemical Health & Safety, American Chemical Society, Sept./Oct. 1996
3. Sources: Kelly, Richard J., Chemical Health & Safety, American Chemical Society, **1996**, Sept, 28-36 Revised 12/97

APPENDIX G: SHOCK SENSITIVE AND EXPLOSIVE CHEMICALS

Shock sensitive refers to the susceptibility of a chemical to rapidly decompose or explode when struck, vibrated or otherwise agitated. Explosive chemicals are those chemicals that have a higher propensity to explode under a given set of circumstances than other chemicals (extreme heat, pressure, mixture with an incompatible chemical, etc.). The label and SDS will indicate if a chemical is shock sensitive or explosive. The chemicals listed below may be shock sensitive or explode under a given number of circumstances and are listed only as a guide to **some** shock sensitive or explosive chemicals. Follow these guidelines:

1. Write the date received and date opened on all containers of shock sensitive chemicals. Some chemicals become increasingly shock sensitive with age.
2. Unless an inhibitor was added by the manufacturer, closed containers of shock sensitive materials should be discarded after 1 year.
3. Wear appropriate personal protective equipment when handling shock sensitive chemicals.

acetylene	fulminate of mercury	nitroguanidine
acetylides of heavy metal	fulminate of silver	nitroparaffins
amatex	ethylene oxide	nitrourea
amatol	ethyl-tetryl	organic nitramines
ammonal	fulminating gold	ozonides
ammonium nitrate	fulminating mercury	pentolite
ammonium perchlorate	fulminating platinum	perchlorates of heavy metals
ammonium picrate	fulminating silver	peroxides
azides of heavy metals	gelatinized nitrocellulose	picramic acid
baratol	Guanyl	picramide
calcium nitrate	guanyl nitrsamino	picratol
chlorate	Guanyltetrazene	picric acid
copper acetylide	Hydrazine	picryl sulphonic acid
cyanuric triazide	nitrated carbohydrate	silver acetylide
cyclotrimethylenetrinitramine	nitrated glucoside	silver azide
dinitrophenol	nitrogen triiodide	tetranitromethane
dinitrophenyl hydrazine	nitrogen trichloride	
dinitrotoluene	Nitroglycerin	
ednatol	Nitroglycide	
erythritol tetranitrate	Nitroglycol	
Mixtures:		
germanium	Tetracene	
hexanitrodiphenylamine	Tetrytol	
hexanitrostilbene	Trimethylolethane	
hexogen	Trimonite	
hydrazoic acid	Trinitroanisole	
lead azide	Trinitrobenzene	
lead mononitroresorcinate	trinitrobenzoic acid	
lead styphnate	Trinitrocresol	
mannitol hexanitrate	Trinitroresorcinol	
sodium picramate	Tritonal	
tetranitrocarbazole	urea nitrate	
References: Safety Data Sheets, various chemical companies		

APPENDIX H: FSU CHEMICAL SAFETY LABORATORY CHECKLIST

FERRIS STATE UNIVERSITY – LAB SAFETY INSPECTION CHECKLIST

Principal Investigator/Faculty	Department	Location (Room & Bldg.):	Inspected By:	Date:
Description of Lab Operations:				

General Safety

Item	Description	Yes	No	N/A
1	Chemical inventory and SDS's maintained and up-to-date.			
2	Current emergency contact information posted in the Information Management System.			
3	A telephone or cell phone is available and emergency contact numbers are posted in the lab			
4	The PI, paid employees, and research staff have completed Lab Safety Training			
5	The PI has evaluated the hazards associated with the procedures, chemicals, and equipment in the lab and, where needed, has made standard operating procedures available to lab staff			
6	The PI provides adequate supervision to research staff, reports all accidents/injuries to CHO			
7	No food and beverages rules are observed			
8	Hand sink (w/ soap), first aid kit and spill kit are available			
9	Special hazards (UV, radiation, biohazards, lasers, etc) clearly identified upon entering the lab			

Housekeeping & Fire Protection

10	Laboratory work surfaces, floors, and storage areas are clean and uncluttered			
11	Unobstructed access to exits, fire extinguishers, safety showers and eyewashes			
12	Electrical cords in good condition, no permanent extension cords, and properly grounded			
13	Sprinkler heads are unobstructed and in good condition			
14	Glassware and equipment are in good condition and free from defects			
15	Flammable materials are stored away from ignition sources			
16	Bulk quantities of flammables stored in flammable storage cabinets			

Chemical Storage

17	All containers are labeled, in good condition, and not leaking			
18	Incompatible materials are segregated			
19	Corrosives and flammables stored below eye level			
20	Peroxide forming agents dated and disposed or tested if past the expiration date			
21	Bench storage of chemicals kept to a minimum			
22	Unnecessary, unused, or outdated materials are removed from labs or storage areas			
23	Cylinders properly secured, stored (fuel & oxygen separated, away from heat), labeled with contents or "empty", and capped when not in use. Hoses and connections in good condition.			
24	Refrigerators storing flammable materials are designed for use with flammable materials			
25	No toxic or poisonous gasses used			
26	Particularly hazardous substances (high acute/chronic toxicity, infectious agents, select carcinogens, reproductive toxins, etc.) are properly identified and stored			

Personal Protection

27	Eye protection and appropriate gloves are available and properly used in all laboratories			
28	Proper dress and closed-toed footwear rules are enforced, lab coats available if necessary			
29	Safety showers & eyewashes are appropriately located and tested			
30	The PI has developed policies for working alone and unattended operations			
31	Fume hoods are operating properly, inspected annually, clean, and not used for storage			
32	Biosafety cabinet is clean, inspected in the past 12 months, UV off			

Waste Handling

33	Staff have made determinations for proper disposal of all waste streams generated in the lab			
34	Waste streams are separated (ex: halogenated solvents, corrosives, liquid or solid, biological)			
35	Hazardous waste containers are clearly labeled and closed when not in use			

36	Syringes and other sharp waste is disposed in a biohazardous sharps container			
----	---	--	--	--

APPENDIX I: TERMINATION OF LABORATORY USE OF HAZARDOUS MATERIALS

Whenever a Laboratory Supervisor (or a person under their charge performing work with hazardous materials in their laboratory) leaves the university or is transferred to a different location, proper disposition of hazardous materials is required. This includes faculty, staff, post-doctoral and graduate students.

If improper management of hazardous materials at closeout requires removal services from an outside contractor, the responsible department will be charged for this service.

Hazardous Chemical Disposal in Laboratories and Containment Areas

The following procedures should be completed before the responsible individual leaves the university or transfers to a different location on campus.

- Assure that all containers of chemicals are labeled with the name of the chemical. All containers must be securely closed. Beakers, flasks, evaporating dishes, etc., should be emptied. Hazardous chemical wastes must not be sewered or trashed; they must be collected for disposal.
- Clean chemicals from glassware and assure proper waste disposal guidelines are followed. Never pour chemical residues down the sink unless it is specified by the Chemical Hygiene Officer that this is the safe and preferred method of disposal.
- Check refrigerators, freezers, fume hoods, storage cabinets, and bench tops for chemical containers and thoroughly clean these locations.
- If another room or facility (such as a freezer or refrigerator, stock rooms, etc.) is shared with other researchers, remove, transfer, or dispose of items used by the departing researcher.
- Contact the Chemical Hygiene Officer for pick-up of hazardous waste at least one week prior to vacating the lab.
- For gas cylinders, remove regulators, replace cap and return to supplier. Gas cylinders used in the containment area must be decontaminated prior to return.

As an alternative to disposal, if the chemical is still usable, transfer the responsibility of the chemical to a supervisor who is willing to take charge of the chemical.

Follow all guidelines for disposal of unwanted chemicals. Hazardous waste chemicals should be placed in the Hazardous waste disposal room, provided:

- All chemical containers are properly labeled as "hazardous waste" and are accompanied with a completely filled out hazardous waste tag.
- All containers are securely closed.

Notify the department when laboratories or containment area/rooms have been cleared.

Transportation of Chemicals on Campus

The following procedures should be completed by individuals who have usable chemicals that are to be moved to a different laboratory.

- Assure that all containers of chemicals are labeled with the name of the chemical. All containers must be securely closed. Beakers, flasks, evaporating dishes, etc., should be emptied. Stock solutions should be transferred to containers intended for use in transportation such as screw cap bottles. Transportation requirements for usable chemicals are the same as that for hazardous waste.
- Chemicals offered for shipment must be grouped together on lab benches or on shelves to facilitate removal.
- For gas cylinders, remove regulators and replace cap. Attach a tag with the name of the person responsible for the material, a contact person, and a phone number.
- A licensed transporter should be contacted to package and deliver the materials to the new location. The Chemical Hygiene Officer will help in making a proper selection.
- Persons intending to transport chemical materials themselves should contact the Chemical Hygiene Officer.

Disposal of Controlled Substances

The United States Drug Enforcement Agency (DEA) issues permits for controlled substances. There are several considerations when disposing of controlled substances.

- Abandonment of a controlled substance is a violation of the DEA permit under which it is held.
- Permission to transfer ownership of a controlled substance must be received from the DEA.
- If controlled substances for which the licensee is unknown are found, contact the Chemical Hygiene Officer.
- Controlled substances being held by a licensed individual and to be surrendered for destruction must be inventoried on DEA Form 41 and mailed to:
- The disposal of controlled substances is coordinated by the CHO and involves the hazardous waste vendor's reverse dispensing program or return to the supplier.

Disposal of Biological Materials

Animal Tissue

- If tissue is held in a liquid preservative, the tissue and liquid should be separated.
- Animal parts and tissues should be placed in a biohazard waste bag for incineration.
- Liquid preservatives usually need to be disposed as a hazardous waste. Contact the CHO for assistance. Do not assume that the preservative can be sewerred.
- If appropriate disposal is uncertain, contact the CHO.
- Defrost and clean refrigerators and freezers if they are empty.
- If samples need to be saved, locate the supervisor to take responsibility for them.

Microorganisms and Cultures

- Use an autoclave to decontaminate all liquid culture waste, and dispose of it as the policy states.
- If the material cannot be decontaminated, place it in a biohazard bag for incineration.
- Clean and disinfect incubators, drying or curing ovens, refrigerators and freezers.
- If samples need to be saved, locate the supervisor to take responsibility for them.

Transportation of Biological Materials on Campus

All biological materials* that are of potential risk to humans and/or animals must be stored and transported in a primary and secondary container. Primary containers can be culture tubes, flasks, vials etc. All containers must meet the following requirements:

- Rigid
- Puncture resistant
- Leak proof
- Impervious to moisture
- Of sufficient strength to prevent tearing or bursting under normal conditions of use and handling
- Sealed to prevent leakage during transport
- Labeled with a biohazard or infectious substance label

All containers should be accompanied by a list of content, the person responsible for this material, a contact person and phone number.

If materials are to be transported in liquid nitrogen or with other protection from ambient or higher temperatures, all containers and packaging should be capable withstanding very low temperatures, and both primary and secondary packaging must be able to withstand a pressure differential of at least 95 kPa and temperatures in the range of -40 ° C to +50 ° C. If the material is perishable, warnings should appear on accompanying documents, e.g., "Keep cool, between +2 ° C and +4 ° C."

For all shipment requirements of biological materials **off campus** contact the Chemical Hygiene Officer.

* **Infectious substances:** viable microorganisms, including a bacterium, virus, rickettsia, fungus, or a recombinant, hybrid or mutant, that are known or reasonably believed to cause disease in animals or humans.

* **Diagnostic specimens:** any human or animal material including but not limited to, excreta, secretions, blood and its components, tissue and tissue fluids.

Radioisotopes

For appropriate close out procedures for Radioactive Materials, please contact the Radiation Safety Officer.

Equipment

If laboratory equipment is to be left for the next occupant, clean or decontaminate it before departing the laboratory. If exhaust or filtration equipment has been used with extremely hazardous substances or organisms, alert the Chemical Hygiene Officer.

If laboratory equipment is to be discarded, be aware that capacitors, transformers, mercury switches, mercury thermometers, radioactive sources, and chemicals must be removed before disposal. Contact the Chemical Hygiene Officer for assistance. See policy regarding disposal of surplus University property:
<https://www.ferris.edu/HTMLS/administration/buspolletter/financial/Disposal-of-Surplus-University-Property.pdf>.

Equipment potentially contaminated with radioisotopes must be surveyed by the Radiation Safety Officer or the Chemical Hygiene Officer prior to release or use by other persons.

Shared Storage Areas

One of the most problematic situations is the sharing of storage units such as refrigerators, freezers, cold rooms, stock rooms, waste collection areas, etc., particularly if no one has been assigned to manage the unit. Departing researchers must carefully survey any shared facility in order to locate and appropriately dispose of their hazardous materials.

Regulatory Impact

Mishandling of hazardous materials can result in citations, fines, and/or loss of right to use hazardous materials. Adverse publicity is also a frequent result.

APPENDIX J: INDUSTRIAL TOXICOLOGY – OVERVIEW

Chemical Toxicology

- **Toxicology:** The study of the nature and action of chemical poisons.
- **Toxicity:** The ability of a chemical molecule or compound to injure a susceptible site in or on the body.
- **Toxicity hazard:** The probability that injury will occur considering the manner in which the substance is used.

Dose-Response Relationship

The potential toxicity (harmful action) of a substance is exhibited only when that substance comes in contact with a biological system. A chemical that may seem "harmless" may evoke a toxic response if added to a biological system in sufficient amount. The toxicity of a chemical is defined by the response that is produced in a biological system.

Routes of Entry into the Body

1. **Inhalation:** Absorption through the respiratory tract. Most important in terms of severity.
2. **Skin absorption or absorption through the mucous membranes.**
3. **Ingestion:** Absorption through the digestive tract. Can occur through eating or smoking with contaminated hands or in contaminated work areas.
4. **Injection:** Introduction of toxin into bloodstream; can occur by needle stick or skin puncture by a sharp object.

Exposure Limits as Related to Routes of Entry

- Most exposure standards are based on the inhalation route of exposure. They are normally expressed in terms of parts per million (ppm) or milligrams per cubic meter (mg/m) concentration in air.
- The Occupational Safety and Health Administration (OSHA) have established Permissible Exposure Limits (PELs) and the American Conference of Governmental Industrial Hygienists (ACGIH) has established Threshold Limit Values (TLV's) for employee exposure limits. Often the PEL and TLV are the same number. In the instances where one is lower than the other, it is prudent to maintain exposures at the lowest level achievable.
- If a significant route of exposure for a substance is through skin contact, the TLV or PEL will have a "skin" notation. Examples are pesticides, carbon tetrachloride, cyanides, ethylenediamine, and thallium.
- For a more complete list of PEL's and TLV's see the ACGIH publication "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices." The latest editions list both TLV's and PELs.

Types of Effects

- **Acute poisoning** is characterized by rapid absorption of the substance when the exposure is sudden and severe. Normally, a single large exposure is involved. Examples are carbon monoxide or cyanide poisoning.
- **Chronic poisoning** is characterized by prolonged or repeated exposures over time. Symptoms may not be immediately apparent. Examples are lead or mercury poisoning, or pesticide exposure.
- **Local** refers to the site of action of an agent where the action takes place at the point or area of contact. The site may be skin, mucous membranes, the respiratory tract, gastrointestinal system, eyes, etc. Absorption does not necessarily occur. Examples are strong acids or alkalis.
- **Systemic** refers to a site of action other than the point of contact and presupposes absorption has taken place. For example, an inhaled material may act on the liver. For example, inhaled benzene affects the bone marrow.
- **Cumulative poisons** are characterized by materials that tend to build up in the body as a result of numerous chronic exposures. The effects are not seen until a critical body burden is reached. Examples are heavy metals.
- **Synergistic or potentiating** effects occur when two or more hazardous materials present at the same time have a resulting action greater than the effect predicted based on the individual substances. For example, workers exposed to benzene may show a direct toxicity in hematopoietic tissue and therefore be more susceptible to oxygen-displacing agents such as carbon monoxide.

Other Factors Affecting Toxicity

- **Rate of entry and route of exposure** - how fast the toxic dose is delivered and by what means.
- **Age** - can affect the capacity to repair damaged tissue.
- **Previous exposure** - can lead to tolerance, increased sensitivity, or make no difference.
- **State of health, medications, physical condition, and life style:** Pre-existing disease can result in increased sensitivity.
- **Environmental factors** - temperature and pressure, for example, can affect exposure.

- **Host factors** - genetic predisposition and the sex of the exposed individual.

Physical Class Effects on Toxicity

When considering the toxicity of gases and vapors, the **solubility of the substance** is a key factor. Highly soluble materials like ammonia irritate the upper respiratory tract. On the other hand, relatively insoluble materials like nitrogen dioxide penetrate deep into the lung. Fat-soluble materials, like pesticides, tend to have longer residence times in the body.

An **aerosol** is composed of solid or liquid particles of microscopic size dispersed in a gaseous medium. The toxic potential of an aerosol is only partially described by its concentration in milligrams per cubic meter (mg/m³). For a proper assessment of the toxic hazard, the size of the aerosol's particles is important. Particles above 1 micrometer tend to deposit in the upper respiratory tract. Particles less than 1 micrometer in diameter enter the lung. Very small particles (< 0.2 5m) are generally not deposited.

Physiological Classifications of Toxic Materials

Irritants are materials that cause inflammation of mucous membranes with which they come in contact.

Inflammation of tissue results from concentration far below those needed to cause corrosion. Long-term exposure to irritants can result in increased mucous secretions and chronic bronchitis. Examples include:

ammonia	phosgene	alkaline dusts - mists	diethyl sulfate
hydrogen chloride	nitrogen dioxide	hydrogen fluoride	Dimethyl sulfate
halogens	Arsenic trichloride	Ozone	phosphorus chlorides

Irritants can also cause changes in the mechanics of respiration and lung function. Examples include:

sulfur dioxide	iodine	acetic acid	sulfuric acid
formaldehyde	acrolein	formic acid	

A **primary irritant** exerts no systemic toxic action because the products formed on the tissue of the respiratory tract are non-toxic or because the irritant action is far in excess of any systemic toxic action. Example: hydrogen chloride.

A **secondary irritant's** effect on mucous membranes is over-shadowed by a systemic effect resulting from absorption. Examples include hydrogen sulfide or aromatic hydrocarbons. Exposure to a secondary irritant can result in pulmonary edema, hemorrhage, and tissue necrosis.

Corrosives are chemicals that may cause visible destruction of or irreversible alterations in living tissue by chemical action at the site of contact. Examples include sulfuric acid, chromic acid, potassium hydroxide, and sodium hydroxide.

Asphyxiants have the ability to deprive tissue of oxygen.

Simple asphyxiants are inert gases that displace oxygen. Examples include:

- nitrogen
- carbon dioxide
- hydrogen
- nitrous oxide

Chemical asphyxiants render the body incapable of utilizing an adequate oxygen supply. They are toxic at very low concentrations (few ppm). Examples include:

- carbon monoxide
- cyanides
- hydrogen sulfide

Primary anesthetics have a depressant effect upon the central nervous system, particularly the brain. Examples include:

- halogenated hydrocarbons
- alcohols

Hepatotoxic agents cause damage to the liver. Examples include:

- carbon tetrachloride
- Nitrosamines
- tetrachloroethane

Nephrotoxic agents cause damage to the kidneys. Examples include:

- halogenated hydrocarbons
- uranium compounds

Neurotoxic agents damage the nervous system. The nervous system is especially sensitive to organometallic compounds and certain sulfide compounds. Examples include:

- trialkyl tin compounds
- thallium
- methyl mercury
- carbon disulfide
- organic phosphorus insecticides
- tetraethyl lead
- manganese

Hematopoietic (blood) system agents either directly affect blood cells or bone marrow. Examples include:

- nitrites
- benzene
- aniline
- toluidine
- nitrobenzene

Pulmonary tissue (lungs) agents can be toxic, through other mean than by immediate irritant action. Fibrotic changes can be caused by free crystalline silica and asbestos. Other dusts can cause a restrictive disease called pneumoconiosis. Examples include:

- coal dust
- cotton dust
- wood dust

A **teratogen** (embryo toxic or fetotoxic agent) is an agent that interferes with normal embryonic development without damage to the mother or lethal effect on the fetus. Effects are not hereditary. Examples include:

- lead
- dibromo dichloropropane

A **mutagen** is a chemical agent that may able to react with nucleophilic structures such as DNA. Mutations can occur on the gene level (gene mutations) when, for example, one nucleotide base pair is change to another. Mutations can also occur on the chromosomal level (chromosomal mutations) when the number of chromosomal units or their morphological structure is altered. Examples of mutagens include most radioisotopes, barium permanganate, and methyl isocyanate.

A **sensitizer** causes a substantial proportion of exposed people to develop an allergic reaction in normal tissue after repeated exposure to the chemical. The reaction may be as mild as a rash (contact dermatitis) or as serious as anaphylactic shock. Examples include:

- epoxides
- amines
- toluene diisocyanate
- nickel compounds
- poison ivy
- formaldehyde
- chlorinated hydrocarbons
- chromium compounds

TARGET ORGAN EFFECTS

The following is a target organ categorization of effects, which may occur from exposure to hazardous chemicals, including examples of signs and symptoms, and chemicals that have been found to cause such effects.

	SIGNS & SYMPTOMS	EXAMPLES INCLUDE
Hepatotoxins (liver)	jaundice, liver enlargement	carbon tetrachloride, nitrosamines, chloroform, toluene, perchloroethylene, cresol, dimethylsulfate
Nephrotoxins (kidney)	edema, proteinuria	halogenated hydrocarbons, uranium, chloroform, mercury, dimethyl sulfate
Neurotoxins (nervous system)	narcosis, behavioral changes, decreased muscle coordination	mercury, carbon disulfide, benzene, carbon tetrachloride, lead, mercury, nitrobenzene
Hematopoietic (blood) system	cyanosis, loss of consciousness.	carbon monoxide, cyanides, nitrobenzene, aniline, arsenic, benzene, toluene
Pulmonary (lung) system	cough, tightness in chest, shortness of breath.	silica asbestos, nitrogen dioxide, ozone, hydrogen sulfide chromium, nickel, alcohol.
Reproductive system (mutations and teratogenesis)	birth defects sterility.	lead, dibromo dichloropropane.
Skin (dermal layer)	defatting of skin, rashes, irritation.	ketones, chlorinated compounds, alcohols, nickel, phenol, trichloroethylene.
Eye or vision	conjunctivitis, corneal damage.	organic solvents, acids, cresol, quinone, hydroquinone, benzyl chloride, butyl alcohol, bases.

APPENDIX K: FSU RESPIRATORY PROTECTION PROGRAM

FSU has established the following policy to ensure that employees and students are protected from adverse exposures to respiratory hazards. The University is committed to maintaining engineering controls that provide an indoor atmosphere free of harmful chemical, physical and biological agents. This policy will apply in situations where those controls are not sufficient and other means of respiratory protection are required.

This program, training, recordkeeping will be administered by the FSU Director of SHERM.

A. SITUATIONS REQUIRING THE USE OF RESPIRATORS.

Respirators are required in any situation where the potential for exposure to a particular airborne contaminant exceeds occupational exposure limits or a hazard assessment determines one to be necessary.

No employee may be exposed to any air contaminant above the levels established by Occupational Safety and Health Administration (OSHA). Employees shall utilize Safety Data Sheets (SDS) or other credible information sources to ensure compliance. Faculty and Staff may not require that a student or employee use a respirator in situations other than those identified in this policy without prior approval of University health and safety staff, who will provide specific guidance. However, voluntary use dust masks is not discouraged (see “dust mask” section below).

This policy covers only the use of face-mounted respirators. Consult the health and safety staff for information on belt-mounted, self-contained, and remote-source respirators and their use.

The University recognizes the following situations when respirator use is required:

- Air monitoring has identified that respiratory hazards are present.
- A hazard assessment identifies that there is a reasonable expectation that an individual could be exposed to respiratory hazards above Permissible Exposure Limits.
- Employees working in areas where contaminant levels may become unsafe without warning, such as emergency response.
- The SDS or chemical label requires the use of a respirator.
- Areas where there is a significant risk that biological agents become aerosolized.
- Spraying of pesticides in greenhouses.

B. RESPIRATORY PROTECTION FOR EMPLOYEES.

Before any employee may begin a job that requires respirator use, the following items must be completed successfully (in the order listed below).

1. Evaluation by a licensed physician using either a physical examination or medical questionnaire. A medical evaluation is required for each employee who is required to wear a respirator, regardless of the duration and frequency of respirator use. The medical evaluation must be conducted by a licensed physician and completed before respirator fit testing and initial respirator use. The medical evaluation is to be done during the employee's work day.

The medical evaluation can be accomplished in either of the following two ways.

- a. Medical Questionnaire. In some situations the physician may only need to review a medical questionnaire without needing to conduct a physical examination. [OSHA's Respirator Medical Evaluation Questionnaire](#) can be completed by the employee and then reviewed by a physician who determines the employee's fitness to wear a respirator. The physician may request an office visit for a physical examination for any reason if he or she feels it is appropriate. The following information must be submitted to the physician:
 - The completed Respirator Medical Evaluation Questionnaire.
 - A SDS for the material to which the employee will be exposed.
 - A copy of this policy.
- b. Physical Medical Examination. The employee visits a physician who will evaluate the employee's physical fitness to wear a respirator. The physician will conduct whatever tests he/she feels are appropriate, but at a minimum will provide information adequate to ensure that the wearer is physically fit to wear the respirator. If the physician is properly equipped, the user seal and fit tests may be conducted at the same time. Upon visiting a physician, the employee must bring the following information:
 - A SDS for the material to which the employee will be exposed
 - A copy of this policy.
 - The specified respirator if user seal and fit test are to be conducted during the physical.

The physician must provide a written opinion of the individual's fitness to wear a respirator and whether or not there are any conditions employee or employer must follow. One copy of the approval shall be placed in the employee's file, and one copy provided to the employee.

The evaluation is required only once, except under the following circumstances:

- c. Physician recommends re-evaluation at a specific interval.
- d. Changes in the workplace that may result in an increase on the physical burden of the employee or significantly increase exposure.
- e. The employee reports suffering distress through wearing a respirator, signs or symptoms relating to respirator use, or a change in health condition that may affect respirator use.
- f. The University determines it is necessary.

The evaluations must be conducted by Birkham Health Center. Prior arrangements need to be made by a supervisor, Human Resources, or health and safety staff.

Upon termination of employment, medical evaluations shall be permanently kept in the employee's personnel file.

2. Training in Respirator Use. All employees required to wear respirators will be trained in the hazards present and proper selection, fit testing, use, and maintenance of respirators. This will be done both before an employee begins the use of a respirator and annually thereafter. All employees will be made aware of the hazards present from all chemicals as part of the University's hazard communication or Lab Safety Program.
3. Checking Fit Prior to Use. Employees must ensure the respirator provides a proper fit. Fit testing can only be performed after the physician has given approval for the employee's respirator use. Also, fit testing and respirator use in general cannot be done if there is substantial facial hair between the skin and the facepiece of the respirator. Proper fit is to be checked as follows:

- (a) User Seal Check Procedure. Each time an employee uses a respirator, proper fit must be checked (see [OSHA User Seal Check Procedures](#)). This is done using either of the following two procedures.
- Positive Pressure Facefit Check. To check, place palm of hand over the exhalation valve cover and exhale gently. Be careful not to disturb the position of the respirator. If the facepiece bulges slightly, and no air leaks between the face and the facepiece are detected, a proper fit has been obtained. If air leakage is detected, reposition the respirator on the face and/or readjust the tension of the elastic straps to eliminate the leakage. Repeat the above steps until a tight seal is obtained. If a proper fit cannot be achieved, the employee may not enter the area but should instead see his/her supervisor.
 - Negative Pressure Facefit Check. To check, place the palms of hands or thumbs over both filters. Be careful not to disturb the position of the respirator. The employee should then inhale gently and hold his/her breath for five to ten seconds. If the facepiece collapses slightly, a proper fit has been obtained. If air leakage is detected, reposition the respirator on the face and/or readjust the tension of the elastic straps to eliminate the leakage. Repeat the above steps until a tight seal is obtained. If proper fit cannot be achieved, the employee cannot enter the area but should instead see his/her supervisor.
- (b) Qualitative Fit Test. Often referred to as an "irritant smoke test." These tests are only to be conducted by SHERM staff who have reviewed the OSHA accepted [Qualitative Fit Test Protocol](#) and after the employee has passed the medical exam and user seal check. These tests are to be performed at least annually, and under the following circumstances: a new respirator is purchased, the employee requests a test, a request by a supervisor, doctor, or the University, and any other condition that may lead to a poor seal of a respirator.

C. RESPIRATOR STORAGE AND MAINTENANCE.

Respirators must be stored inside a cabinet or drawer with a door to keep out dust, sunlight, extreme heat or cold, moisture, or chemicals. Respirators should be stored so facepieces and exhalation valves will rest in a normal position to prevent rubber or plastic from reforming into an abnormal shape.

The respirator body shall be replaced whenever found to be faulty (i.e. cracked or broken face seal or body). A valve or headband shall be replaced as soon as any performance loss is noticed.

Each employee is responsible for keeping his/her respirator clean and in good condition, and returning it to the respirator cabinet in a sealed bag, which is usually provided with a new respirator. Avoid sealing wet respirators in airtight bags due to potential for mold growth. Respirators must be cleaned and disinfected regularly using antiseptic wipes. If employees must share a respirator, it must be disinfected after each use.

1. Number of Respirators. One respirator (and only one) will be issued to each person required to wear a respirator. The University will provide the respirator and cartridges at no cost to the employee. Each respirator will be clearly marked with the person's name to prevent the sharing or exchanging of respirators.
2. Inspection of the Effectiveness of the Respirator Program. All managers, supervisors, and safety managers are responsible for making regular checks of work area conditions and employee practices to make sure the respirator program is effective. Inspections will ensure that proper

respirators and cartridges are used, respirators are used at appropriate times, and that they are clean, clearly labeled and well maintained.

3. Temporary Changes in Conditions. If air sampling reveals unusually high levels of any potentially harmful material, this respirator policy may be temporarily modified by the University safety personnel.

D. RESPIRATORS AND CARTRIDGES.

The following respirators have been approved by the University.

	<u>3M 6000 SERIES</u>
Respirator Body – Small, Medium or Large	6100, 6200 or 6300
Full Facepiece Respirator (S-L)	6700-6900
P-100 HEPA Filter	2093 (magenta)
P-100 HEPA Organic Vapor / Acid Gas Filter	60923 (yellow/magenta)

With wear, the body will have to be periodically replaced to maintain the respirator's filtering capacity.

1. Filters. Always consult the product Safety Data Sheet and the cartridge manufacturer to ensure proper cartridge selection prior to use. **NO FILTER WILL PROVIDE PROTECTION IN OXYGEN DEFICIENT ATMOSPHERES.** There are two main types of filters that will typically be used:

- (a) P-100 HEPA Filter. The first is a HEPA (High Efficiency Particulate) filter. This filter removes airborne particulates and aerosol contaminants such as silica, sawdust, most biological contaminants, or liquid particles (non-oil) that do not emit harmful vapors. A respirator fitted with this filter will provide protection from dusts, fumes, or mists by capturing coarse and fine particles on the filter.

HEPA filters have served their useful life and must be replaced when visibly dirty, when breathing resistance becomes excessive, or when the user experiences taste, smell or irritation related to the particles being filtered.

- (b) P-100 HEPA Organic Vapor/Acid Gas Filter. This type of filter cartridge protects against certain organic vapors, acid gas and particulates that may be found in laboratories, pharmaceutical and chemical manufacturing. When properly fitted these provide respiratory protection from certain organic vapors, chlorine, hydrogen chloride, sulfur dioxide, or hydrogen sulfide or hydrogen fluoride and particulates at concentrations up to 10 times the Permissible Exposure Limit. Not to be used for formaldehyde, ammonia, mercury vapor or methylamine.

Follow the [manufacturer's recommendations](#) for use and replacement recommendations. In general, if the user experiences taste, smell or irritation related to the chemical being used the filter should be replaced.

E. DUST MASKS.

1. Required Use of Dust Masks. In no case does a dust mask provide adequate protection against inhalation of airborne contaminants above occupational exposure levels. Typical respiratory

hazards at the University do not require the use of dust masks; however any employee can request to wear a dust mask for his/her own comfort. The University will keep a supply of NIOSH-approved dust masks and provide them at no expense to the employee.

If an employee is required to wear a dust mask, the requirements stated in this policy for employee respiratory protection must be followed. That includes medical evaluation and training, but not fit testing requirements.

2. Voluntary Use of Dust Masks. If a supervisor chooses to allow employees to wear dust masks voluntarily, they must do the following:
 - a. Ensure that the dust mask will not itself create a safety or health hazard to the individual wearing it.
 - b. Provide the individual with the information provided in [OSHA's Information for Employees Using Respirators When Not Required](#).

F. **INDOOR AIR MONITORING.**

The University will conduct representative sampling when there is reason to believe that an employee may be exposed to airborne contaminants above OSHA's Permissible Exposure Limits (PEL) or action levels during a typical work day. All sampling and monitoring shall be coordinated through the University's health and safety staff. Individuals who are sampled will receive written results of their sampling within two weeks of receipt of the report from the laboratory.

1. Monitoring will be conducted at the following intervals:
 - c. Initial Monitoring. When an area begins or significantly alters the use of a chemical suspected to exceed the OSHA PEL or Action Level, a sample from all job classifications with potential exposure above the Action Level will be taken. Additionally, any significant changes in production, process, handling procedures, etc. that might increase the level of contaminants in the atmosphere makes retesting necessary.
 - d. Routine Monitoring. At appropriate intervals, routine monitoring may be performed to ensure the levels are within the acceptable limits. All job classifications that are required to wear a respirator and some that could have potential exposure will be sampled. If results above the Action Level are detected, sampling will be done every six months until operational changes bring levels within acceptable limits.
 - e. Complaint Monitoring. If there are reports of signs or symptoms that may indicate overexposure, such as respiratory or skin conditions associated with exposure to airborne contaminants, the affected individuals must notify their supervisor immediately. Health and safety personnel will determine whether monitoring will be necessary.
2. Working Areas. The University will maintain the general working area with exposures well below the PEL. If any areas exceed that level, the appropriate respiratory protection must be worn until corrective engineering controls are implemented. These would usually include operational changes, improved ventilation, or facility improvements.

If a particular area is expected to be above the PEL, all entrances must be posted with an appropriate warning sign.

3. Exposure Levels.

Consult the SDS for exposure levels of airborne contaminants.

- (a) Action Level. An eight hour time weighted average concentration below which no further action is needed.
 - (b) PEL. The maximum eight hour time weighted average concentration that an employee can be exposed to without wearing a respirator. Monitoring results between the Action Level and PEL will be resampled within six months of the sampling event. If monitoring results show exposure above the PEL, full-time respirator use will be required for that job until satisfactory results are received. This requirement will be waived only if there is compelling evidence that the test was not representative of the employee's exposure.
 - (c) STEL. The maximum concentration of airborne contaminants that an employee can be exposed to in a 15 minute period. Job classifications where employee exposure may exceed the STEL require respirator use while performing these jobs.
 - (d) Maximum Concentration. The level above which special types of respirators must be used. Areas exceeding the Maximum Concentration must improve their engineering controls to reduce these levels.
4. Recordkeeping. The University must maintain any records concerning employee exposure, monitoring, and training at their facility. Corporate will keep the following records for the necessary retention time:

<u>Records</u>	<u>Retention Time</u>
Exposure monitoring results	30 years
Training	30 years (file with exposure results)
Medical Surveillance	Duration of employment plus 30 years.
Respirator Fit Test	Until replaced by a more recent record.

APPENDIX L: VOLUNTEERS IN LABS TEMPLATE^[TD14]

Date:

Volunteer Name:

Address:

City/State/Zip:

RE: Ferris State University (“University”) Lab Volunteer

Dear Volunteer:

Thank you for your interest in volunteering to assist in the _____ laboratory under the direction of _____.

The University is obligated to provide a safe working environment for volunteers, adhering to the same standards it has for its employees. Before you can begin your volunteer assignment you will be required to complete appropriate lab safety training.

Your roles and responsibilities as a laboratory volunteer are as follows:

With regard to general liability, the University Board of Trustees indemnifies properly appointed volunteers the same as a University employee pursuant to the requirements and conditions outlined in Business Policy Letter: *Legal Representation and Indemnification*.

Please consider the aforementioned expectations and complete the *Laboratory Volunteer Profile, Disclosure, Consent, Assumption of Risk, Release and Waiver of Liability, and Covenant not to Sue Form* with the required information and return the signed copy to me. Upon receipt, we can schedule you for lab safety training, provide you with a schedule, and provide a date for you to begin your volunteer assignment.

Again, I want to thank you for volunteering your time to the University and supporting its important mission in educating and shaping the lives of our students.

Sincerely,

FSU Laboratory Volunteer Profile, Disclosure, Consent, Assumption of Risk, Release and Waiver of Liability, and Covenant not to Sue Form **("Form")**
(Department to keep on file)

Volunteer Name: (please print): _____ ("Volunteer")
Over Age 18: Yes____ No____

Address: _____ City: _____ State: ____ Zip Code: _____

Telephone (include area code): _____ Cell Phone: _____ Email: _____

Emergency Information:

Contact Name: _____ Telephone (include area code): _____

Email (if known): _____ Relationship to Volunteer: _____

Thank you for volunteering your time and talent to Ferris State University ("University") in support of its important mission of educating and shaping the lives of our students.

A University volunteer is an individual who performs work or provides services in support of University activities without the expectation of compensation. Volunteers may perform a variety of services, however the University does not intend for volunteers to perform or displace work that is presently being performed by University employees.

Volunteers acting on behalf of the University are expected to adhere to University policies, including, but not limited to, those policies concerning laboratory safety, alcohol and drug use, vehicle use, personal conduct, fiscal propriety, sexual harassment, diversity, and non-discrimination. The University may, as a result of inappropriate conduct or other valid reasons, remove volunteers from a University laboratory.

Volunteers are not considered employees and are not covered by workers' compensation disability benefits. Therefore volunteers are personally responsible for the expense of any medical care received for injuries incurred because of volunteer service to the University. Volunteers are not eligible for unemployment benefits.

The University may require you to complete and pass a criminal background check before your volunteer assignment begins.

Disclosure of Associated Risks

The University endeavors to provide a safe working environment for volunteers, adhering to the same standards it has for its employees. Therefore, there are dangers and risks to which you may be exposed as a volunteer in a University laboratory. These dangers and risks may include, but are not limited to, the possibility of slight or severe bodily injury, or death, hazardous substances (chemicals/biologicals, etc.), physical hazards (very hot or cold temperatures, laser light, electromagnetic frequencies), and: _____

_____ ("dangers and risks").

I, the undersigned, am aware of the dangers and risks directly or inherently involved in volunteering in a University laboratory. I voluntarily agree to assume all responsibility and risk of injury to myself or my property arising from, but not limited to, my volunteering in a University laboratory and related activities including all dangers and risks of accidents, illness, bodily injury, and property damage.

I, individually and on behalf of my heirs, successors, assigns, and personal representatives, hereby covenant not to sue and release and waive the University, its trustees, employees, agents, officers, and representatives ("Releasees") from any and all liability, claims, and actions I may have for damages, losses or injuries I may sustain to my person or property arising out of my volunteering in a University laboratory, except if damage, loss, or injury is directly caused by the gross negligence or willful wanton misconduct of the Releasees.

I HAVE CAREFULLY READ THIS ENTIRE FORM. I FULLY UNDERSTAND THE FORM AND ITS PROVISIONS, AND AGREE TO BE BOUND BY ITS TERMS AND CONDITIONS. I INTEND FOR THIS FORM TO BE VALID AND BINDING.

Signature of Volunteer

Date

Name (Please Print)

If the above signed is not of legal age (18) at the date of signing, this form must be signed by the Volunteer's parent or legal guardian.

As the parent or legal guardian of the Volunteer whose signature appears above, I have read and understand the conditions outlined above, have given my child or ward permission to become a volunteer, and agree to be bound by the conditions outlined above as if I myself had signed above.

Signature of Parent/Legal Guardian

Date

Name (Please Print)

****NOTE TO DEPARTMENTS****

Signed originals should be retained by the Department for a period of one-year post completion of the volunteer assignment.

Approved – FSU General Counsel – 1/16/2020

APPENDIX M: LIST OF DEFINITIONS

ACGIH -- The American Conference of Governmental Industrial Hygienists is a voluntary membership organization of professional industrial hygiene personnel in governmental or educational institutions. The ACGIH develops and publishes recommended occupational exposure limits each year called Threshold Limit Values (TLV's) for hundreds of chemicals, physical agents, and includes Biological Exposure Indices (BEI).

Action Level -- A concentration designated in 29 CFR part 1910 for a specific substance, calculated as an eight-hour time-weighted average, which initiates certain required activities such as exposure monitoring and medical surveillance.

Acute -- Severe, often dangerous exposure conditions in which relatively rapid changes occur.

Acute Exposure -- An intense exposure over a relatively short period.

ANSI -- The American National Standards Institute is a voluntary membership organization (run with private funding) that develops national consensus standards for a wide variety of devices and procedures.

Asphyxiant -- A chemical (gas or vapor) that can cause death or unconsciousness by suffocation. Simple asphyxiants such as nitrogen either use up or displace oxygen in the air. They become especially dangerous in confined or enclosed spaces. Chemical asphyxiants, such as carbon monoxide and hydrogen sulfide, interfere with the body's ability to absorb or transport oxygen to the tissues.

Autoclave -- A device to expose items to steam at a high pressure in order to decontaminate the materials or render them sterile.

Biohazard -- Infectious agents that present a risk or potential risk to the health of humans or other animals, either directly through infection or indirectly through damage to the environment.

Boiling Point -- The temperature at which the vapor pressure of a liquid equals atmospheric pressure or at which the liquid changes to a vapor. The boiling point is usually expressed in degrees Fahrenheit. If a flammable material has a low boiling point, it indicates a special fire hazard.

"C" or Ceiling -- A description usually seen in connection with a published exposure limit. It refers to the concentration that should not be exceeded, even for an instant. It may be written as TLV-C or Threshold Limit Value--Ceiling (See also THRESHOLD LIMIT VALUE).

Carcinogen -- A substance that may cause cancer in animals or humans.

C.A.S. Number -- Identifies a particular chemical by the Chemical Abstracts Service, a service of the American Chemical Society that indexes and compiles abstracts of worldwide chemical literature called "Chemical Abstracts."

Chemical Hygiene Officer -- An employee who is designated by the employer and who is qualified by training and experience, to provide technical guidance in the development and implementation of the provisions of the Chemical Hygiene Plan. This definition is not intended to place limitations on the position description or job classification that the designated individual shall hold within the employer's organizational structure.

Chemical Hygiene Plan -- A written program developed and implemented by the department which sets forth procedures, equipment, personal protective equipment and work practices that are capable of protecting students, instructors and other personnel from the health hazards presented by the hazardous chemicals used in that particular workplace.

Chronic exposure -- A prolonged exposure occurring over a period of days, weeks, or years.

Combustible -- According to the DOT and NFPA, COMBUSTIBLE liquids are those having a flash point at or above 100deg.F (37.8deg.C), or liquids that will burn. They do not ignite as easily as flammable liquids. However, combustible liquids can be ignited under certain circumstances, and must be handled with caution. Substances such as wood, paper, etc., are termed "Ordinary Combustibles."

Compressed Gas -- A gas or mixture of gases that, in a container, will have an absolute pressure exceeding 40 psi at 70°F or 21.1°C. A gas or mixture of gases having, in a container, an absolute pressure exceeding 104 psi at 130°F or 54.4°C, regardless of the pressure at 70°F. A liquid having a vapor pressure exceeding 40 psi at 100°F or 37.8°C.

Concentration -- The relative amount of a material in combination with another material. For example, 5 parts (of acetone) per million (parts of air).

Corrosive -- A substance that, according to the DOT, causes visible destruction or permanent changes in human skin tissue at the site of contact or is highly corrosive to steel.

Cutaneous/Dermal -- Pertaining to or affecting the skin.

Cytotoxin -- A substance toxic to cells in culture, or to cells in an organism.

Decomposition -- The breakdown of a chemical or substance into different parts or simpler compounds. Decomposition can occur due to heat, chemical reaction, decay, etc.

Designated Area -- An area that may be used for work with “select carcinogens,” reproductive toxins or substances, which have a high degree of acute toxicity. This area may be the entire laboratory or an area under a device such as a laboratory hood.

Dermatitis -- An inflammation of the skin.

Dilution Ventilation -- See GENERAL VENTILATION.

DOT -- The United States Department of Transportation is the Federal agency that regulates the labeling and transportation of hazardous materials.

Dyspnea -- Shortness of breath, difficult or labored breathing.

EPA -- The Environmental Protection Agency is the governmental agency responsible for administration of laws to control and/or reduce pollution of air, water, and land systems.

EPA Number -- The number assigned to chemicals regulated by the Environmental Protection Agency (EPA).

Epidemiology -- The study of disease in human populations.

Erythema -- A reddening of the skin.

Evaporation Rate -- The rate at which a material is converted to vapor (evaporates) at a given temperature and pressure when compared to the evaporation rate of a given substance. Health and fire hazard evaluations of materials involve consideration of evaporation rates as one aspect of the evaluation.

Explosive -- A chemical that causes a sudden, almost instantaneous release of pressure, gas, and heat when subjected to sudden shock, pressure, or high temperature.

Flammable Gas -- A gas that, at an ambient temperature and pressure, forms a flammable mixture with air at a concentration of 13 percent by volume or less; or, a gas that, at an ambient temperature and pressure forms a range of flammable mixtures with air wider than 12 percent by volume, regardless of the lower limit.

Flammable Liquid -- According to the DOT and NFPA, a flammable liquid is one that has a flash point below 100deg.F. (See FLASH POINT).

Flammable Solid -- A solid, other than a blasting agent or explosive, that is liable to cause fire through friction, absorption of moisture, spontaneous chemical change or retained heat from manufacturing or processing, or which can be ignited readily and when ignited burns so vigorously and persistently it creates a serious hazard.

Flash Point -- The lowest temperature at which a liquid gives off enough vapor to form an ignitable mixture and burn when a source of ignition (sparks, open flames, etc.) is present. Two tests are used to determine the flashpoint: open cup and closed cup. The test method is indicated on the SDS after the flash point.

Fume -- A solid particle that has condensed from the vapor state.

Gas -- Chemical substances that exist in the gaseous state at room temperature.

General Ventilation -- Also known as general exhaust ventilation, this is a system of ventilation consisting of either natural or mechanically induced fresh air movements to mix with and dilute contaminants in the workroom air. This is not the recommended type of ventilation to control contaminants that are highly toxic, when there may be corrosion problems from the contaminant, when the worker is close to where the contaminant is being generated, and where fire or explosion hazards are generated close to sources of ignition (See LOCALEXHAUST VENTILATION).

Grams per Kilogram (g/Kg) -- This indicates the dose of a substance given to test animals in toxicity studies. For example, a dose may be 2 grams (of substance) per kilogram of body weight (of the experimental animal).

Hazardous Chemicals -- Any chemical for which there is significant evidence that acute or chronic health effects may occur in exposed personnel. The term "health hazard" includes chemicals that are carcinogens, toxins, irritants, corrosives, sensitizers or other agents that can damage the lungs, skin, eyes, or mucous membranes.

Ignitable -- A solid, liquid, or compressed gas waste that has a flashpoint of less than 140deg.F. Ignitable material may be regulated by the EPA as a hazardous waste, as well.

Incompatible -- The term applied to two substances to indicate that one material cannot be mixed with the other without the possibility of a dangerous reaction.

Ingestion -- Taking a substance into the body through the mouth as food, drink, medicine, or unknowingly as on contaminated hands or cigarettes, etc.

Inhalation -- The breathing in of an airborne substance that may be in the form of gas, fumes mists, vapors, dusts, or aerosols.

Inhibitor -- A substance that is added to another to prevent or slowdown an unwanted reaction or change.

Irritant -- A substance that produces an irritation effect when it contacts skin, eyes, nose, or respiratory system.

Laboratory -- A facility where relatively small quantities of hazardous materials are used on a non-production basis.

Laboratory Scale -- Work with substances in which the containers used for reactions, transfers, and other handling of substances are designed to be easily and safely manipulated by one person.

Laboratory-type Hood -- A device constructed and maintained to draw air from the laboratory and to prevent or minimize the escape of air contaminants into the laboratory.

Laboratory Use of Hazardous Materials -- The handling or use of chemicals in which the following conditions are met: (1) Chemical manipulations are carried out on a laboratory scale. (2) Multiple chemical procedures or chemicals are used. (3) The procedures involved are not part of a production process. (4) Protective laboratory practices and equipment are available and in common use to minimize the potential for personnel exposure to hazardous chemicals.

Laminar Air Flow -- Air flow in which the entire mass of air within a designated space move with uniform velocity in a single direction along parallel flow lines with a minimum of mixing.

Lethal Concentrations₅₀ -- The concentration of an air contaminant (**LC₅₀**) that will kill 50 percent of the test animals in a group during a single exposure.

Lethal Doses₅₀ -- The dose of a substance or chemical that will (**LD₅₀**) kill 50 percent of the test animals in a group within the first 30 days following exposure.

Local Exhaust Ventilation (Also known as exhaust ventilation.) -- A ventilation system that captures and removes air contaminants at the point they are being produced before they escape into the workroom air. The system consists of hoods, ductwork, a fan, and possibly an air-cleaning device. Advantages of local exhaust ventilation over general ventilation include: removing the contaminant rather than diluting it; less airflow making it a more economical system over the long run; and conservation or reclamation of valuable materials. However, the system must be properly designed with the correctly shaped and placed hoods, correctly sized fans and correctly connected ductwork.

Lower Explosive Limit (LEL) (Also known as Lower Flammable Limit-LFL) -- The lowest concentration of a substance that will produce a fire or flash when an ignition source (flame, spark, etc.) is present. It is expressed in percent of vapor or gas in the air by volume. Below the LEL or LFL, the air/contaminant mixture is theoretically too "lean" to burn (See also UEL).

Melting Point -- The temperature at which a solid changes to a liquid. A melting range may be given for mixtures.

Mutagen -- Anything that can cause a change (or mutation) in the genetic material of a living cell.

Narcosis -- Stupor or unconsciousness caused by exposure to a chemical.

NFPA -- The National Fire Protection Association is a voluntary membership organization whose aims are to promote and improve fire protection and prevention. NFPA has published 16 volumes of codes known as the National Fire Codes. Within these codes is Standard No. 704, "Identification of the Fire Hazards of Materials." This system rates the hazard of a material during a fire. These hazards are divided into health, flammability, and reactivity hazards and appear in a well-known diamond system using from zero through four to indicate severity of the hazard. Zero indicates no special hazard and four indicates severe hazard.

NIOSH -- The National Institute for Occupational Safety and Health is a Federal agency that among its various responsibilities trains occupational health and safety professionals conducts research on health and safety concerns, and tests and certifies respirators for workplace use.

Occupational Safety and Health Administration (OSHA) -- A Federal agency under the Department of Labor that publishes and enforces safety and health regulations for most businesses and industries in the United States.

Odor Threshold -- The minimum concentration of a substance at which a majority of test subjects can detect and identify the substance's characteristic odor.

Oxidation -- The process of combining oxygen with some other substance or a chemical change in which an atom loses electrons.

Oxidizer -- Is a substance that gives up oxygen easily to stimulate combustion of organic material.

Oxygen Deficiency -- An atmosphere having less than the normal percentage of oxygen found in normal air. Normal air contains 21% oxygen at sea level.

Permissible Exposure Limit (PEL) -- An exposure limit that is published and enforced by OSHA as a legal standard. PEL may be either a time-weighted-average (TWA) exposure limit (8 hour), a 15-minute short-term exposure limit (STEL), or a ceiling (C). The PELs are found in Tables Z-1, Z-2, or Z-3 of OSHA regulations 1910.1000. (See also TLV).

Personal Protective Equipment -- Any devices or clothing worn by the worker to protect against hazards in the environment. Examples are respirators, gloves, and chemical splash goggles.

Physical Hazard -- A chemical that has scientifically valid evidence proving it to be a combustible liquid, a compressed gas, explosive, flammable, an organic peroxide, an oxidizer, pyrophoric, unstable (reactive) or water-reactive.

Polymerization -- A chemical reaction in which two or more small molecules combine to form larger molecules that contain repeating structural units of the original molecules. A hazardous polymerization is the above reaction with an uncontrolled release of energy.

RAD -- The unit of absorbed dose equal to 100 ergs per gram or 0.01 joules per kilogram of absorbing material.

Reactivity -- A substance's susceptibility to undergoing a chemical reaction or change that may result in dangerous side effects, such as explosion, burning, and corrosive or toxic emissions. The conditions that cause the reaction, such as heat, other chemicals, and dropping, will usually be specified as "Conditions to Avoid" when a chemical's reactivity is discussed on a SDS.

Reproductive Toxins -- Chemicals that affect the reproductive capabilities including chromosomal damage (mutations) and effects on fetuses.

Respirator -- A device that is designed to protect the wearer from inhaling harmful contaminants.

Respiratory Hazard -- A particular concentration of an airborne contaminant that, when it enters the body by way of the respiratory system or by being breathed into the lungs, results in some bodily function impairment.

Select carcinogens are chemicals listed by MIOSHA as carcinogens, by the National Toxicology Program (NTP) as "known to be carcinogens" and by the International Agency for Research on Cancer (IARC) as Group 1 carcinogens. Also included are chemicals or processes listed in either Group 2A or 2B by IARC or under the category "reasonably anticipated to be carcinogens" by NTP and that cause statistically significant tumor incidence in experimental animals in accordance with any of the following criteria:

After inhalation exposure of 6-7 hours per day, 5 days per week, for a significant portion of a lifetime to dosages of less than 10mg/ml³

After repeated skin application of less than 300 mg/kg of body weight per week

After oral dosages of less than 50 mg/kg of body weight per day

Sensitizer -- A substance that may cause no reaction in a person during initial exposures, but afterwards, further exposures will cause an allergic response to the substance.

Short Term Exposure Limit -- Represented as STEL or TLV-STEL, this is the maximum concentration to which workers can be exposed for a short period of time (15 minutes) for only four times throughout the day with at least one hour between exposures. In addition, the daily TLV-TWA must not be exceeded.

"Skin" -- This designation sometimes appears alongside a TLV or PEL. It refers to the possibility of absorption of the particular chemical through the skin and eyes. Thus, protection of large surface areas of skin should be considered to prevent skin absorption so that the TLV is not invalidated.

Systemic -- Spread throughout the body; affecting many or all body systems or organs; not localized in one spot or area.

Teratogen -- An agent or substance that may cause physical defects in the developing embryo or fetus when a pregnant female is exposed to that substance.

Threshold Limit Value -- Airborne concentrations of substances devised by the ACGIH that represents conditions under which it is believed that nearly all workers may be exposed day after day with no adverse effect. TLV's are advisory exposure guidelines, not legal

standards that are based on evidence from industrial experience, animal studies, or human studies when they exist. There are three different types of TLV's: Time Weighted Average (TLV-TWA), Short Term Exposure Limit (TLV-STEL), and Ceiling (TLV-C). (See also PEL).

Time Weighted Average -- The average time, over a given work period (e.g. 8-hour workday) of a person's exposure to a chemical or an agent. The average is determined by sampling for the contaminant throughout the time period. Represented as TLV-TWA.

Toxicity -- The potential of a substance to exert a harmful effect on humans or animals and a description of the effect and the conditions or concentration under which the effect takes place.

Trade Name -- The commercial name or trademark by which a chemical is known. One chemical may have a variety of trade names depending on the manufacturers or distributors involved.

Unstable (Reactive) -- A chemical that, in its pure state or as commercially produced, will react vigorously in some hazardous way under shock conditions (i.e., dropping), certain temperatures, or pressures.

Upper Explosive Limit -- Also known as Upper Flammable Limit is the highest concentration (expressed in percent of vapor or gas in the air by volume) of a substance that will burn or explode when an ignition source is present. Theoretically, above this limit the mixture is said to be too "rich" to support combustion. The difference between the LEL and the UEL constitutes the flammable range or explosive range of a substance. That is, if the LEL is 1ppm and the UEL is 5ppm, then the explosive range of the chemical is 1-ppm to 5ppm. (See also LEL).

Vapor -- The gaseous state of substances, which are normally in the liquid or solid state (at normal room temperature and pressure). Vapors evaporate into the air from liquids such as solvents. Solvents with low boiling points will evaporate.

Vapor Pressure -- The pressure that a solid or liquid exerts when it is in equilibrium with its vapor at a given temperature.

Water-reactive -- A chemical that reacts with water to release a gas that is either flammable or presents a health hazard.